



FÉDÉRATION INTERNATIONALE
DE MOTOCYCLISME

**TECHNICAL RULES
CROSS-COUNTRY RALLIES**

2020

*RÈGLEMENTS TECHNIQUES
RALLYES TOUT TERRAIN*



Technical Rules Cross-Country Rallies

2020

Règlements Techniques Rallyes Tout-Terrain

Version 3
Applicable as from 19.10.2020

YEAR 2020		
Version	Applicable as from	Modified paragraphs
0	1.02.2020	
1	20.02.2020	01.61
2	20.07.2020	81.01 / 89.04.03 /91.10
3	19.10.2020	01.84
4		

Table of contents

01.01	INTRODUCTION.....	4
01.03	FREEDOM OF CONSTRUCTION	4
01.05	CATEGORIES AND GROUPS OF MOTORCYCLES.....	4
01.07	CLASSES.....	5
01.11	MEASUREMENT OF CAPACITY	7
01.17	SUPERCHARGING	8
01.18	TELEMETRY.....	8
01.21	DESIGNATION OF MAKE	9
01.23	DEFINITION OF A PROTOTYPE	9
01.25	GENERAL SPECIFICATIONS	9
01.26	DEFINITION OF A FRAME OF A SOLO MOTORCYCLE	10
01.27	STARTING DEVICES	11
01.29	OPEN TRANSMISSION GUARDS	11
01.31	EXHAUST PIPES.....	11
01.33	HANDLEBARS.....	12
01.35	CONTROL LEVERS	12
01.37	THROTTLE CONTROLS	13
01.39	FOOTRESTS	13
01.41	BRAKES	13
01.43	MUDGUARDS AND WHEEL PROTECTION	14
01.45	STREAMLINING	14
01.47	WHEELS, RIMS, AND TYRES.....	14
01.50	ADDITIONAL SPECIFICATIONS FOR ELECTRIC POWEREDVEHICLES	16
01.53	ADDITIONAL SPECIFICATIONS FOR SIDECARS	21
01.55	NUMBER PLATES.....	23
01.56	LIGHTING, WARNING EQUIPMENT AND SPEEDOMETERS	24
01.58	ADDITIONAL SPECIFICATIONS FOR 450CC	24
01.59	ADDITIONAL* SPECIFICATIONS FOR QUADS	26
01.61	ADDITIONAL SPECIFICATIONS FOR SIDE BY SIDE VEHICLES ...	30
01.63	FUEL AND LUBRICANT	30
01.65	EQUIPMENT AND PROTECTIVE CLOTHING DURING PRACTICE AND RACE.....	39
01.67	WEARING OF HELMETS	39
01.69	HELMET OPERATIVE INSTRUCTIONS	40
01.70	RECOGNISED HELMET APPROVAL MARKS.....	41
01.73	NATIONAL COLOURS FOR HELMETS	42
01.75	BADGE OF THE FIM	44
01.76	NUMBER SASHES (BIBS).....	44
01.77	TECHNICAL VERIFICATIONS	44
01.78	DANGEROUS MACHINES	50
01.79	SOUND CONTROL.....	51
	SSV TECHNICAL REGULATION.....	59

DIAGRAMS

Any references to the male gender in this document are made solely for the purpose of simplicity, and refer also to the female gender except when the context requires otherwise.

01.01 INTRODUCTION

The term motorcycle covers all vehicles having, in principle, less than four wheels, propelled by an engine and designed essentially for the carriage of one or more persons of which one is the rider of the vehicle. The wheels must normally be in contact with the ground except momentarily or in certain exceptional circumstances. Furthermore, in order to traverse certain surfaces one or all of the wheels can be replaced with skis, rollers or chains.

01.03 FREEDOM OF CONSTRUCTION

A motorcycle must conform to the requirements of the FIM regulations, to the Supplementary Regulations, as well as to a number of specific conditions that the FIM may require for certain competitions. No restriction is placed on the make, construction or type of motorcycle used.

All solo motorcycles (Group A) must be constructed in such a way that they are entirely controlled by a rider. Motorcycles with Sidecars (Group B) must be constructed to carry a passenger.

01.05 CATEGORIES AND GROUPS OF MOTORCYCLES

Motorcycles are divided into categories which must be observed for all meetings and world record attempts.

In principle, it is forbidden for different categories, groups and classes to compete in the same race, unless the Supplementary Regulations state otherwise.

Category I

Motorcycles propelled by the action of one wheel in contact with the ground.

Category II

Special vehicles propelled by the action of one or two wheels in contact with the ground but which are not covered by the conditions of Category I.

Group A1 - Solo Motorcycles

2-wheel vehicles making only one track on the ground.

Group B1

Vehicles with three wheels, making two tracks on the ground, consisting of a motorcycle making one track and a sidecar for a passenger making the other track.

Group B2

Vehicles with three wheels, making two or three tracks on the ground in the direction of forward travel, with a permanently attached Sidecar forming a complete integral unit.

If three tracks are made, the centre-lines of the two tracks made by the motorcycle wheels must not be more than 75 mm apart. A track is determined by the longitudinal centre-line of each of the vehicle's wheels in the direction of forward travel.

Category III

Vehicles propelled by the action of multiple driving wheels in contact with the ground in only one direction.

Group C - Special 2 wheel driven motorcycles

Group D - Special 3 wheel, 2 wheel driven motorcycles

Group E - Snowmobiles

Group F - Sprinters and Dragsters

Group G - Quad racers (propelled by the action of two wheels)

Group H - Quad racers (propelled by the action of four wheels)

Group J – Electric Powered Vehicles (EPVs, see Art. 01.50)

01.07 CLASSES

Groups are again separated into classes according to cylinder capacities as detailed below. Generally, these classes must be observed for all meetings.

See also Arts. 080.7.1 of the 2020 FIM Cross-Country Rallies World Championship Regulations, for details.

Category I

Group A1 - Solo Motorcycles

Class (cc)	over (cc)	up to(cc)
------------	-----------	-----------

50	-	50
80	50	85
100	85	100
125	100	125
175	125	175
250	175	250
450	250	450
500	450	500
750	500	750
1000	750	1000
1300	1000	1300

Groups B1, B2 - Sidecars

Same as groups A1 and A2 over 175 cc.

Category II

Same classes as Category I, Group A1.

Category III

Same classes as Category I, Group A1.

****Please refer to Art. 80.7.1 Categories, Groups, Classes and Trophy of the 2020 FIM Cross-Country Rallies World Championship Regulations. (extract hereunder)***

All motorcycles will be according to Category I, Group A1 and Category II, Group C (Art. 01.07), with the following specifications:

07.01 Categories/Groups/Classes are as follows:

- **Category 1: RallyGP (Art. 01.58)**
 - Group 1: Moto-Rally World Championship (Up to 450cc)**
- **Category 2: Rally2 (Art. 01.58)**
 - Group 1: Moto-Rally World Cup (Up to 450cc)**
 - Group 2: Moto-Enduro World Cup**
 - Group 3: Quad World Cup (Art. 01.59)**
- **Category 3: SSV World Cup (Up to 1050cc) – (Art. 01.60)**

The following Classes will be implemented in Category 1 and 2*:

- **Class 1: Women World Cup**
- **Class 2: Junior World Cup**
- **Class 3: Veteran Trophy**

***In 2020, only classes from the Category 1 will be awarded.
An Adventure Trophy will be introduced for riders in the Category 2 for Group 1 and 3.**

07.02 Details for the 450 cc Class (See also Art.01.58):

All motorcycles will be according to Category I, Group A1 and Category II, Group C (Art. 01.07), with the following details:

- **FIM Cross-Country Rallies World Championship:**

**Category 1 - Rally GP - Group 1: Moto-Rally motorcycles;
based either on 'one' type unit ('proto'-type) or production based.**

- **FIM Cross-Country Rallies World Cup:**

**Category 2: Rally2 – Group 1: Moto-Rally motorcycles;
(same as above)**

**Category 2: Rally2 – Group 2: Moto-Enduro motorcycles;
based on models from a manufacturer's catalogue only.**

Extra requirement for Moto Enduro: Normal on-board instruments and extra navigation equipment shall be fixed on the front fork, triple clamps or on a support fixed on the steering head. A protective screen to shield the instruments is permitted (& recommended).

01.11 MEASUREMENT OF CAPACITY

11.11 Reciprocating movement engine, "Otto" Cycle

The capacity of each engine cylinder is calculated by the geometric formula which gives the volume of a cylinder; the diameter is represented by the bore, and the height by the space swept by the piston from its highest to lowest point:

$$\text{Capacity} = \frac{D^2 \times 3.1416 \times C}{4}$$

where D = bore
and C = stroke

When a cylinder bore is not circular the cross sectional area must be determined by a suitable geometrical method or calculation, then multiplied by the stroke to determine capacity.

When measuring, a tolerance of 1/10 mm is permitted in the bore. If with this tolerance the capacity limit is exceeded for the class in question, a further measurement should be taken with the engine cold, to 1/100 mm limits.

11.13 Rotary engines

The capacity of an engine which determines the class in which the motorcycle shall compete in a meeting shall be calculated by:

$$\text{Capacity} = \frac{2 \times V}{N}$$

where V = total capacity of all the chambers comprising the engine
and N = number of turns of the motor necessary to complete one cycle in a chamber.

This engine is classified as a 4-stroke.

11.15 Wankel system

For Wankel system engines with a triangular piston, the capacity is given by the formula:

$$\text{Capacity} = 2 \times V \times D$$

where V = capacity of a single chamber
and D = number of rotors

This engine is classified as a 4-stroke.

01.17 SUPERCHARGING

Supercharging by means of a device of any kind is forbidden in all meetings.

An engine whether 2-stroke or 4-stroke coming within any one of the recognised classes (determined by the capacity of the working cylinder) shall not be considered as supercharged when in respect of one engine cycle, the total capacity measured geometrically, of the fuel charging device or devices, including the capacity of the working cylinder (if used for injecting the fuel), does not exceed the maximum capacity of the class in question.

01.18 TELEMETRY

Information must not be transmitted in any way to or from a moving motorcycle.
An official signalling device may be required on the machine.
Automatic lap timing devices are not considered as "telemetry".

Automatic lap timing devices must not disrupt any official time keeping methods and equipment.

01.21 DESIGNATION OF MAKE

When two manufacturers are involved in the construction of a motorcycle the name of both must appear on the machine as follows:

- The name of the chassis manufacturer
- The name of the engine manufacturer

01.23 DEFINITION OF A PROTOTYPE

A prototype motorcycle is a vehicle which must conform to the safety requirements as required by the FIM Sporting Code and Appendices applicable to the type of competition for which it is to be used.

01.25 GENERAL SPECIFICATIONS

The following specifications apply to all vehicles of the groups indicated and to all types of competitions except where otherwise stated in the corresponding section of the FIM Sporting Code.

They should also be applied to all national competitions unless the FMNR (National Motorcycling Federation) has otherwise directed.

Further specifications for some competitions may also be required and these will be detailed in either the appropriate FIM Appendix or in the Supplementary Regulations for the competition in question.

All vehicles from the World Championship 450cc and Quad categories must conform in all respects to the 1968 Vienna Convention, even if the country in which the machine was manufactured is not a signatory to that Convention, and be registered for road use.

Each motorcycle/quad must be equipped with at least one or several fixed water tanks with a total and minimum capacity of a fixed water tank of 3 litres, made and fixed in a secure way. The Chief Technical Steward/FIM Technical Director will have the final decision for the acceptance of the water tank solution and the fixing method. (Plastic bottles or cans cannot be considered as fixed water tank).

All motorcycles/quads must carry the necessary survival equipment as requested in the Cross-Country Rallies World Championship Regulations, Art. 080.28.

Concerning material verification, in case of doubt, a sample or the part in question shall be taken and analysed at a Material Testing laboratory.

25.01 Use of titanium

The use of titanium in the construction of the frame, the front forks, the handlebars, the swinging arms, the swinging arm spindles and the wheel spindles is forbidden.

The use of light alloys for wheel spindles is also forbidden.

The use of titanium alloy nuts and bolts is allowed.

25.03 Carbon fibre

The use of carbon fibre reinforced materials is authorised (with the exception of handlebars and wheel rims).

25.04 Ceramic materials

The use of ceramic parts is forbidden.

25.05 Other equipment

No signal of any kind may pass between a moving motorcycle and any person, including radio and Bluetooth communication. The exception is for the signal from the time keeping transponder, the tracking system as provided by the Organiser, automatic lap timing devices or approved on-board cameras (with prior written approval from the Championship Promoter/Organiser, which cannot be granted for helmet mounted cameras).

25.06 Number of cylinders

The number of cylinders in an engine is determined by the number of combustion chambers.

25.07

If separate combustion spaces are used they must be connected by an unrestricted passage of minimum cross sectional area at least 50% of the total inlet port area.

01.26 DEFINITION OF A FRAME OF A SOLO MOTORCYCLE

The structure or structures used to join any steering mechanism at the front of the machine to the engine/gear box unit and to all components of the rear suspension.

26.01

Every motorcycle in the 'parc-fermé' must be equipped with a side-stand. The side-stand must be fitted, either on the frame or on the swing arm.

01.27 STARTING DEVICES

Starting devices for the engine are compulsory.

01.29 OPEN TRANSMISSION GUARDS

29.01

A guard must be fitted to the countershaft sprocket.

29.02

A chain guard must be fitted in such a way to prevent trapping between the lower chain run and the final driven sprocket at the rear wheel.

01.31 EXHAUST PIPES

Exhaust pipes and silencers must fulfil all the requirements concerning sound control (see also Art. 01.79).

31.01

The axis of the silencer end must be parallel (tolerance 15°) to the two principal longitudinal planes of the vehicle. The extremity of the silencer must not pass the vertical tangent of the rear tyre.

31.02

The edge of the silencer shall not be dangerous in case of accidental contact with the riders or helpers. In case of quads, the exhaust pipe of the silencer must be protected by a rounded edge of minimum 4 mm.

31.03

Exhaust fumes must be discharged towards the rear but not in such a manner as to raise dust, foul the tyres or brakes, or inconvenience the passenger (in the case of sidecars), or any other rider.

31.04

On a Sidecar machine the exhaust must discharge horizontally and towards the rear, at a maximum angle of 30° to the axis of the machine.

31.05

Any NON-ORIGINAL valve systems installed on the exhaust system with a view to influencing (or modifying) the sound level meter test is forbidden. Only exhaust valve systems (e.g. Exup) provided by the manufacturer on the manifold are authorised. The setting is free.

01.33 HANDLEBARS

33.01

The width of handlebars must be not less than 600 mm and not more than 850 mm.

33.02

The handlebars must be equipped with a protection pad on the cross bar. Handlebars without a cross member must be equipped with a protection pad located in the middle of the handlebars, covering widely the handlebars clamps.

33.03

Handlebar clamps must be very carefully radiused and engineered so as to avoid any fracture points in the handlebar.

33.04

Exposed handlebar ends must be plugged with a solid material or rubber covered.

33.06

When hand protectors are used, these must be made of a shatter-resistant material and have a permanent opening for the hand.

33.07

Handlebars made of composite materials are not authorised.

33.08

Repair by welding of light alloy handlebars is prohibited.

33.09

Solid stops (when on full-lock, other than steering dampers) must be fitted. These must ensure a minimum clearance of 30 mm between the handlebar with levers and the tank to prevent trapping the rider's fingers.

01.35 CONTROL LEVERS

35.01

All handlebar levers (clutch, brake, etc.) must be in principle ball ended (diameter of this ball to be at least 16 mm). This ball can also be flattened, but in any case the edges must be rounded (minimum thickness of this flattened part 14 mm). These ends must be permanently fixed and form an integral part of the lever. If the gear lever consists of a tube, then its edge must be rounded.

35.03

Each control lever (hand and foot levers) must be mounted on an independent pivot.

35.04

The brake lever if pivoted on the footrest axis must work under all circumstances, such as the footrest being bent or deformed.

01.37 THROTTLE CONTROLS

37.01

Throttle controls must be self-closing when not held by the hand. All air intakes into the cylinder must pass through the throttle body. No other means allowing ambient air into the inlet track of the cylinder head are allowed.

37.03

Solo motorcycles must be equipped with a functional ignition kill switch or button mounted on either right or left side of handlebar (within reach of the hand while on the hand grips), that cut the power to the engine.

Quads must be equipped with a safety ignition cut-out switch which must be permanently attached to the rider right wrist by a non-elastic, spiral cable, as short as possible.

01.39 FOOTRESTS

Footrests must be solidly fixed or of a folding type but in this case must be fitted with a device which automatically returns them to the normal position, and an integral protection is to be provided at the end of the footrest which must have at least 8 mm radius (see Diagrams). The footrest teeth shall not be sharp. As of 2020, the height of the footrest teeth must be 10 mm maximum.

01.41 BRAKES

41.01

All motorcycles must have at least 2 efficient brakes (one on each wheel, front and rear) operated independently and operating concentrically with the wheel.

41.02

Vehicles in Group B must be fitted with at least 2 efficient brakes operating on at least 2 of the wheels and be operated independently and operating concentrically with the wheels.

01.43 MUDGUARDS AND WHEEL PROTECTION

Motorcycles must be fitted with mudguards.

43.01

Mudguards must project laterally beyond the tyre on each side.

43.02

The front mudguard must cover at least 100° of the circumference of the wheel. The angle formed by one line drawn from the front edge of the mudguard to the centre of the wheel and one drawn horizontally through the centre of the wheel must be between 45° and 60°.

43.03

The rear mudguard must cover at least 120° of the circumference of the wheel. The angle formed by two lines, one drawn from the rear edge of the mudguard to the centre of the wheel and one drawn horizontally through the centre of the wheel shall not exceed 20°.

The angle (20° max.) for the rear mudguard shall be measured with the rider sitting on the motorcycle (See Diagram S).

01.45 STREAMLINING

A 'full' fairing or 'complete' bodywork is not allowed.

Radiator covers (shields) must be made of flexible materials only (e.g. plastics).

01.47 WHEELS, RIMS, AND TYRES

47.01

All tyres will be measured mounted on the rim at a pressure of 1 kg/sq.cm (14 lb./sq.in); measurements are taken at a tyre section plane with a 90° angle with the ground plane.

47.02

Any modification to the rim or spokes of an integral wheel (cast, moulded, riveted) as supplied by the manufacturer (other than for rims with spokes, or valve and security bolts) is prohibited, except for tyre retention screws sometimes used to prevent the tyre movement relative to the rim. If the rim is modified for these purposes, bolts, screws, etc., must be fitted.

47.03

The front and rear tyre dimensions are free with reference to diameter and width.

47.04

Tyres with metal studs, spikes, chains or any other anti-skid devices are not permitted. Scoop or paddle tyres (continuous radial rib) are forbidden.

47.05

Only tyres normally available from commercial or retail sources are authorised.

Modifying the tyre is not authorised. It is forbidden to treat tyres with chemicals, cut or groove them, use tyre warmers or any other means which may alter the shape, minimum Shore hardness, construction or other characteristics.

The tyres shall appear on the tyre manufacturers range catalogue or tyre specification lists available to the general public.

They shall be approved according to UN Vehicle Regulation 75 Rev. 2 (2010) with the following specific features:

- Category of use (5.2): it shall be "snow" or "special" or "All terrain"
- Speed category symbol (5.4): M (130 Km/h) or above
- Load capacity index (5.5): 45 (165 Kg) or above.

It is recommended that the tyres be used according to the European Tyre and Rim Technical Organisation (ETRTO) guidelines.

The E approval mark and number as defined by the UN Vehicle Regulation R75 must be present on both the front and rear tyre sidewalls.

The DOT approval mark is also accepted.

Any marking on the tyre reporting "FIM" approved or similar is forbidden for new production dates (from 2018).

47.06

The tread pattern specifications of the rear tyre are free. However, Art. 47.05 applies in full.

01.50 ADDITIONAL SPECIFICATIONS FOR ELECTRIC POWERED VEHICLES

50.01 INTRODUCTION

The technical concept is reserved for motorcycles propelled by non-thermal energies with zero toxic/noxious emissions and by the action of one wheel in contact with the ground.

Amendments to these technical regulations may be made at any time in order to ensure fair competitions.

50.02 GENERAL EPV CLASS REQUIREMENTS

EPVs refer to two- and/or three-wheeled autonomous electric powered motorcycles, having traction on one or both wheels (with an unpowered sidecar if applicable).

The number of electric motors is limited to one.

50.02.1 Race Procedures

(Race procedures to be defined by the Sporting Commission concerned).

50.02.2 Race Format (Guidelines – actual race format depends on the discipline and battery life)

Minimum race length: 20 minutes

Maximum race length: 30 minutes

50.02.3 Charging the accumulator

Energy supply will be provided in the paddock at the times and locations determined by the race Organiser.

Charging may only be done with the energy supply provided by the race Organiser.

The charging system must be separate from the machine and comply with all electrical safety requirements including thermal overload trip, fusing and be equipped with an earth leakage protection breaker.

50.02.4 Pit Stop

Riders will be allowed to define their own method of energy renewal subject to safety and practical considerations subject to the approval of the race Organiser.

Riders who wish to have a pit stop must declare the process and technology to the FIM Technical Director/Chief Technical Steward for a safety evaluation. All information will be treated with strict confidentiality.

50.02.5 Transponder timing

All machines must be equipped with an official transponder.

50.02.6 Technical Verifications

As a condition of entry, all safety items on-board the motorcycle must be precisely described and presented at the Technical Verifications.

The Technical Steward shall check both the machine and the rider for compliance with the technical specifications, as well as the employment of good engineering construction practice, and the presence of adequate electrical insulation and weatherproofing.

Damaged machines must be returned to the Technical Verifications area for examination after race or practice. In such circumstances it is the responsibility of the competitor to ensure both his machine and clothing have been rechecked and approved before further use in the event. If stickers/marks are used, a new sticker/mark must be in place.

It is the responsibility of the rider to ensure that a machine used in competition is electric, mechanically and structurally in a safe condition.

In case of a dispute, the decision of the FIM Technical Director will be final.

50.02.7 Conformity

It is the duty of each competitor to show the Technical Stewards of the meeting that his vehicle fully complies with these rules and the rules governing the meeting, in their entirety at all times.

50.03 General vehicle specifications

50.03.1 Requirements

All motorcycles must comply in every respect with all the requirements for racing as specified in the FIM General Technical Specifications, unless otherwise specified below.

The power circuit consists of all those parts of the electrical equipment which are used to propel the motorcycle. The on-board circuit consists of all those parts of the electrical equipment which are used for signalling, lighting or communication.

The accumulator is defined as any on-board equipment used for the storage of electrical energy supplied by the charging unit.

Recovering energy generated by the kinetic energy of the vehicle is permitted.

The use of any external source of energy in any form whatsoever with the aim of improving the performance of the vehicle is strictly prohibited.

50.03.2 Number Plates and Colours

See Art. 01.55.

50.03.3 Handlebars

See Art. 01.33.

50.03.4 Control levers

See Art. 01.35.

50.03.5 Foot Rest/Foot Controls

See Art. 01.39.

50.03.6 Wheel and rims

See Art. 01.47.

50.03.7 Tyres

See Art. 01.49.

50.03.8 Streamlining

See Art. 01.45.

50.03.9 Machine Weight

Neither a minimum nor a maximum weight is/are applied.

50.03.10 Overall Dimensions

The specific dimensions for the vehicles of this discipline apply.

50.03.11 Inclination

It must be possible for a motorcycle not being loaded, to be inclined to an angle of 40 degrees from the vertical, without any part of it other than the tyre coming in contact with the ground.

In race conditions, the vehicle must be capable of affecting a standing start on an uphill slope with a gradient of 18%.

50.04 Electrical safety

It must be ensured that the components used cannot cause injury under any circumstances, either during normal operation or in foreseeable cases of malfunction. It must be ensured that the components used for protecting persons or objects can reliably fulfil their function for an appropriate length of time.

50.04.1 Electrical components


All parts of the electrical equipment must be protected to at least the equivalent of IP 44 type protection (dust proof and splash proof). Exposed connectors/wires must be protected against abrasion in case of accident (side covers).

50.04.2 Power bus maximum voltage

The maximum allowed voltage in the main power bus is 400VDC or 285VAC. A secondary power bus may be used to supply energy to the critical systems at a maximum voltage of 20VDC or 14VAC.

50.04.3 High voltage symbols

Symbols warning of 'HIGH VOLTAGE' must be displayed on or near the electrical equipment protective covers; all symbols must comprise a black flash of lightning inside a yellow triangle with a black border. The sides of the triangle must measure at least 8 cm, but may be larger if practical.



50.04.4 Insulation

Every part of the electrical equipment must be electrically insulated relative to all live components and system ground. Maximum default current is 20mA.

Wiring insulators can be required to be checked at any time by the FIM Technical Director/Chief Technical Steward. Double insulation will be required in high voltage or high current wires. Technical datasheets of the wires used will prevail under all circumstances.

Plus and minus wires from the battery must be insulated with respect to the chassis to withstand battery maximum voltage at least.

All electrically conducting non-live parts must be connected with the system ground.

In cases where the voltage of the power circuit exceeds 36VDC, the power circuit must be separated from the on-board circuit by an appropriate insulator.

Insulating material not having sufficient mechanical resistance, i.e. paint coating, enamel, oxides, fibre coatings (soaked or not) or insulating tapes are not accepted.

50.04.5 Power Indicator

When the vehicle is in a ready state, there must be two clearly visible indicators, one light on the instrument panel/on the front close the center of the handlebar and one light on the rear of the vehicle.

The rear light must be red and visible from at least 10 m away, from the rear or the side.

50.04.6 General circuit breaker – 'Emergency Stop'

The general circuit breaker must disconnect from the cut-off switch and discharge the main bus voltage below 60V. This system will be referred to as general circuit breaker or "Emergency stop".

Low power accumulators provided for low voltage circuits, e.g. auxiliary circuits, do not have to be isolated by the general circuit breaker (Emergency Stop) provided that they are completely isolated from the main power accumulators.

50.04.7 Fuses (over-current trip switches)

An over-current trip switch is a device which automatically interrupts the electrical current in which it is installed if the level of this current exceeds a defined limit value for a specific period of time.

Fuses must under no circumstance replace the general circuit breaker (Emergency Stop).

50.04.8 Capacitors

Voltage across capacitors belonging to the power circuit should fall below 65 volts within 5 seconds after the general circuit breaker is opened or the over current trips of the accumulator are blown.

50.04.9 Power control

A 'self-closing' throttle (power control) must be applied.

50.04.10 Accumulator (storage battery)

The type, dimensions and weight of accumulator/s cannot be changed between official practices and race.

All on-board electrical equipment, unless consisting of items originally powered by dry batteries, small accumulators or their own solar cells, must receive its energy supply from the vehicle's official accumulators.

IMPORTANT: As a condition of entry, a Material Data Safety Sheet must be supplied with the race entry for the machine, including all relevant details as to the accumulator chemistry, human and environmental hazards, handling and specific fire risks and precautions.

50.04.11 Accumulator fastening

The accumulator must be installed securely inside the vehicle and be protected against short-circuits and leakage. The accumulator must be attached to the frame or chassis using metal clamps with an insulating covering.

The fixing method must be designed in such a way that neither the accumulator nor the fastening device itself nor its anchorage points can come loose, even when subjected to a crash. A solid partitioning bulkhead must separate the location of the accumulator from the rider.

Each accumulator box must provide its own cooling and/or venting system. In modular battery systems, a heat shield is strongly recommended between modules, by means of an adiabatic shield or intumescent.

The accumulator installation must ensure that in the event of accumulator cell leakage or explosion, the contents are kept away from the rider and do not interfere in any way with the rider's vision or the safe handling of the machine.

01.53 ADDITIONAL SPECIFICATIONS FOR SIDECARS

53.01

The Sidecar must be fixed to the motorcycle in at least three points, if it is not an integral part of the chassis.

The fixing points must not allow movement at the joints (articulated Sidecars are strictly forbidden). If the angle of the inclination is changeable, it must be locked in such a way that the fixing method is completely secured and not only clamped on.

A structure of crossed belts or a metallic grid must be fitted to fill the opening between the wheels and the sidecar, to prevent the rider's foot from accidentally touching the ground.

The fuel tank(s) must be sufficiently and independently protected from the ground.

53.06

The drive shall be transmitted to the ground only through the rear wheel of the motorcycle.

53.07

The distance between the tracks left by the centre lines of the rear motorcycle wheel and the Sidecar wheel must be at least: 800 mm and not more than 1150 mm.

53.09

To reduce the torque in the steering, a maximum displacement of 75 mm is permitted between the front and the rear wheel.

53.10

The steering of the front wheel must be accomplished without any intermediate articulated steering joints directly by a classic telescopic fork or a swinging arm fork with the wheel supported equally each side (long or short leading link type). All other types of front wheel steering and suspension are forbidden.

53.11

The minimum dimensions of a Sidecar available for passenger accommodation are:

Length: 1 000 mm - Width: 400 mm

Height of the screen protecting the passenger: 300 mm minimum.

53.12

The minimum ground clearance of a laden Sidecar when measured must not be less than 175 mm.

53.13

The position of the engine is optional, except that it must be positioned in front of the rear wheel.

The centre line of the engine corresponds to the crankshaft axis (for longitudinal engines) and to the centre line of the cylinders block (for transverse engines). The centre line of the engine shall not exceed more than 160 mm beyond the centre line of the rear wheel of the motorcycle.

If the engine and gearbox are mounted on plates, the minimum thickness of the steel plates must be 4 mm, and 5 mm for light alloy plates.

53.14

Handlebars must be firmly secured to the forks. They must be at a height above the mid-point in the seat.

The motorcycle must have a steering head which must be fitted like the handlebar, and must not be attached to the unsuspended part of the front wheel suspension.

53.15

The seat must have minimum dimensions of 300 mm x 150 mm and must be fixed at a minimum height of 300 mm above the Sidecar floor.

53.16

For Sidecars, the Sidecar wheel must be covered or protected with a solid material.

53.17

Referring to the longitudinal axis of the motorcycle, the exhaust pipe shall not protrude beyond the width of the sidecar (if on the sidecar side) or protrude by more than 330 mm (if on the motorcycle side).

If the exhaust pipe is on the sidecar side, it must not exceed the vertical line drawn at a tangent to the rear edge of the Sidecar platform.

01.55 NUMBER PLATES

Number plates are required for Cross-country rallies.

The Organiser shall provide each rider with a set of identification plates comprising 1 front plate and 2 side plates called number plates. The exact sizes and positions of these number plates will be explained in the SR.

The number plates shall be affixed visibly at the front and on the rear sides of the motorcycle. They shall in no circumstances cover, throughout the duration of the event, even partly, the registration number of the motorcycle.

55.07

The figures must be clearly legible and like the background must be painted in matt colours to avoid reflection from sunlight. The minimum dimensions of the letters being:

- Height of the number 140 mm
- Width of figure 80 mm
- Width of the stroke 25 mm
- Space between two figures 15 mm

55.08

The English form for numbers must be used. That is single vertical line for the "one" and a simple sloping line without a horizontal line for the "seven". (See Diagram O).

55.09

All other number plates or markings on a motorcycle liable to cause confusion with the number must be removed before the start of a competition.

55.12 Number plate colours

The background colours and figures vary according to the class of motorcycle and the type of competition, the main rules being indicated in the Supplementary Regulations for each meeting.

The colours must be matt, following the RAL colour table, example :

YELLOW	1003
PURPLE	4006
BLACK	9005
WHITE	9010

55.13

In case of a dispute concerning the legibility of numbers, the decision of the Technical Steward will be final.

01.56 LIGHTING, WARNING EQUIPMENT AND SPEEDOMETERS

Motorcycles and their equipment must comply with the national legal requirements for road traffic of the country in which the vehicle is registered and with other rules specified in the Supplementary Regulations.

The electric generator must operate continuously and normally with respect to current and voltage requirements to run front and rear lights during the competition and at post competition control. The electrical connections must be retained.

Lighting equipment for all categories must conform in every way to the International Convention on road traffic, moreover the original headlights and rear lights may be modified or replaced. Extra lights may be added

01.58 ADDITIONAL SPECIFICATIONS FOR 450CC

These vehicles are registered (allowed to be used on roads open to traffic) and can be modified and/or equipped for Off-Road Cross-Country Rallies competition.

All motorcycles will be according to Category I, Group A1 and Category II, Group C (see also Art. 01.07).

58.01 Engine capacity

World Championship, -Cup: 450cc category:
Single cylinder engines up to 450cc 2T or 4T

58.02 Engine

The engine number must remain visible at all times.

Engine preparation is free

During the event, an “engine change” means removing the engine from the frame. Engine “A”, originally fitted in the frame of the bike can be removed from the frame to be repaired and be replaced by engine “B”. Engine “A” may be repaired during the Event on condition that the engine crankcase marked during the preliminary technical inspection remains the same.

Repairs to the engine’s “top end” (cylinder + cylinder head) are free during the event. All intervention to the “bottom-end” (inside the crankcases) will be considered as a change of engine.

A minimum of one bolt/nut used to fix the engine must be drilled in order to attach a seal embracing the frame.

The engine may be removed from the frame to repair a problem not related to the crankcase. This may be done only under the supervision of the Technical Steward. The Technical Steward only can cut and replace the seals without being penalised.

58.02 Frame and ancillaries

The main frame must be marked with the original Vehicle Identification Number (VIN). The frame number (VIN) must remain visible at all times.

The frame shall not be replaced during the event. The frame may be repaired under the supervision of the Technical Steward.

58.03 Fuel tank(s)

The total fuel capacity carried in all tanks is 35 litres maximum.

58.04 Weight

Unrestricted.

01.59 ADDITIONAL* SPECIFICATIONS FOR QUADS

***The present Art. 01.59 prescribes additional rules for Quads, while the rest of the book applies.**

These vehicles shall be registered (allowed to be used on roads open to traffic).

Top speed is limited to 130km/h

Quads are set in two Groups :

**01.59.1 Group G/ Quad Racers:
 propelled by the action of two wheels (2 wheel driven).**

Engine must be produced in a series and available on the market. Cylinder, cylinder head may be modified, with the exception of the crankcase, but must fulfil the FIM Technical Rules for Cross-Country Rallies Quads category.

The chassis is free (in design), material: steel

**01.59.2 Group H/ Quad Racers:
 propelled by the action of four wheels (4 wheel driven).**

Refer to Article 01.07 Classes for definition.

The engine minimum production quantities for engines shall be: 200 units*

***The minimum required production quantities refer to units with identical equipment.**

Evidence of engine production quantities may be required by FIM, certified by the manufacturer's auditing firm and/or any other institution which may provide reliable documentation written in English.

59.01 Engine capacity

Group G:

- from 250cc up to 350cc for two cylinder, 2-stroke engines
- up to 500cc for single cylinder, 2-stroke engines
- up to 750cc for single cylinder, 4-stroke engines.

Group H:

- up to 900cc for single or twin cylinders, 4-stroke engines.

59.02 Engine

The engine must be produced from a recognised and FIM licenced manufacturer.

The engine number (stamped on the crankcase) must remain visible at all times.

The following engine specifications and components may be altered from the original model:

- 1) Cylinder head:**
Intake and exhaust tracts surfaces may be polished. No addition of material is allowed.
The gasket is free and compression ratio can be modified.
- 2) Camshafts and camshaft sprockets are free.**
Valve springs can be replaced but titanium springs are forbidden.
- 3) Pistons, pistons rings, pins and clips: may be altered or replaced from those fitted to the engine.**
- 4) Exhaust system:**
Exhaust pipes and silencers may be altered or replaced.
- 5) Clutch: An aftermarket or modified clutch is permitted.**
- 6) Radiator and/or oil cooler may be altered or replaced, additional radiators and oil cooler may be added.**
- 7) Oil pumps and oil liners may be altered or replaced. Oil lines containing positive pressure, if replaced, must be of metal reinforced construction with swaged or treaded connectors.**
- 8) Oil tanks may be added or modified.**
- 9) Air filter may be altered or replaced.**
- 10) Fuel pump may be modified or replaced.**
- 11) Ignition / Engine Control System (ECU), hardware and software may be modified or changed.**
- 12) Generator, alternator, electric starter may be modified or replaced.**
- 13) Secondary transmission is free.**

During the event, an 'engine change' means removing the engine from the frame. Engine 'A' originally fitted in the frame of the bike can be removed from the frame to be repaired and be replaced by engine 'B' Engine 'A' may be

repaired during the event on the condition that the engine crankcase(s) marked during the preliminary technical inspection remain(s) the same.

Repairs to the engine's 'top end' (cylinder + cylinder head) are free during the event. All intervention to the 'bottom-end' (inside the crankcases) will be considered as a change of engine.

A minimum of one bolt/nut used to fix the engine must be drilled in order to attach a seal embracing the frame.

The engine may be removed from the frame to repair a problem not related to the crankcase. This intervention may be done only after formal request and under the supervision of the Technical Steward. Only the Technical Steward can cut and replace the seals without the participant being penalised.

59.03 Steering

The machine can operate on the front wheels only.

59.04 Chassis and ancillaries

Shock absorbers and associated springs are free.

Wheelbase, front and rear track are free but the overall width is defined by Art. 59.11.

The main chassis must be marked with the original Vehicle Identification Number (VIN). The frame number (VIN) must remain visible at all times.

The chassis shall not be replaced during the event. The frame may be repaired under the supervision of the Technical Steward.

For Group H only:

The main chassis may only be altered by addition of material, no material can be removed (except original engine fixing points if an alternative unit is installed).

The position on the chassis of steering pipe, swing arm, suspension linkage mounting points must remain as in the production Quad.

The rear sub-frame can be modified, but the type of material must remain as in the production model and the weight cannot be lower.

Fairing and body can be modified or replaced.

Seat may be modified or replaced.

Battery may be changed but the nominal energy must be equal or higher than the original one.

Footrests and foot controls may be modified or replaced.

59.05 Number plates

Four number plates are required:

- 1 plate fixed to the front of the machine at the level of the head lamp, facing forward.
- 1 double-side rear plate made of flexible material set on the safety bar placed behind the saddle of the quad.

59.06 Suspensions

All the mountings of the front and rear suspension units, suspension arms and the steering spindle are retained by a safety wire or a splitpen.

For Group H only:

Steering linkages and suspension arms may be modified or replaced. The FIM may require demonstrating that the new parts present equivalent or higher mechanical properties to the original ones.

59.07 Brakes, wheels and rims

Disc brakes, callipers and associated pipes can be changed.

The rear wheel rim diameter cannot exceed 12 inches in Group G and 15 inches in Group H. Wire spokes are not authorised.

Every front wheel must have a single, functional brake installed on each axle and be operated by a handlebar mounted lever.

At the rear, the vehicle must have a brake on each wheel or a brake installed jointly on the rear wheel axle, operated either by a lever on the handlebar or by a foot pedal.

Wheels may be replaced but not modified. Magnesium alloys and carbon-reinforced wheels are forbidden.

59.08 Mudguards

The front and rear wheels must be covered by mudguards made of flexible materials, covering each wheel over an area of minimum 30 degrees.

59.09 Fuel tank(s)

Supplementary fuel tanks are allowed but must be at least 25 mm (1 inch) away with relation to the edges of the protective barrier.

The maximum fuel tank capacity (counting all tanks) is 45 litres.

Original fuel tanks can be modified or replaced but the fixing points on the chassis and the fixing system must be as in the original model. Supplementary fuel tanks are allowed.

59.10 Protection (Diagram Q)

The secondary chain transmission must be equipped with a cover/shield protecting both the chain sprocket and the brake disc.

A compulsory countershaft sprocket guard must cover the sprocket by 30% minimum and prevent the rider's hand/foot becoming trapped.

The complete length of the lower chain run must be shielded by a guard or a protection tube, securely fixed.

A crash 'bar' or 'guard' must be fixed at the front and the rear of the vehicle.

A protective barrier (or 'guard') of a round profile (minimum diameter: 25 mm or 1 inch) must be installed on each side of the vehicle. This protective barrier must be fitted in such a way that it is in alignment with the wheels to eliminate entanglement. There shall be no prominent (sharp) parts.

A structure of crossed belts or a metallic grid must be fitted to fill the opening between the wheels and the barrier, to prevent the riders' foot from accidentally touching the ground.

59.11 Dimensions

The width cannot exceed 1300mm for group G and 1400mm for group H.
The maximum height at the rider's seat level is 950mm for group G and 1000mm for group H (with all liquids at operational level and full fuel tank, and without the rider).

01.61 ADDITIONAL SPECIFICATIONS FOR SIDE BY SIDE VEHICLES

See Appendix A

01.63 FUEL AND LUBRICANT

All vehicles must be fuelled with

- unleaded fuel (from public pump station or race type) OR
- a mixture of unleaded fuels OR
- a mixture of unleaded fuel(s) and lubricant in the case of 2-stroke engines.

The unleaded fuel or the mixture of unleaded fuels used must comply with the FIM specifications as set out in Art. 63.01.

The mixture of unleaded fuel(s) and lubricant must comply with the FIM specifications as set out in Art. 63.02.

Riders/teams must declare to the FIM Technical Director (or the FMNR Chief Technical Steward when there is no FIM Technical Director appointed) the make and type of fuel to be used during practices and race(s), upon presentation of the rider/team's motorcycle(s) at the initial Technical Verifications. They are also recommended to provide a certificate issued by the fuel company which certify that the fuel has been tested and is in conformity with FIM specifications.

Fuel companies which supply 'race' fuels (fuels other than those obtained at public pump stations) to participating teams/riders must test their fuel at Intertek Schlieren (Switzerland) against all the FIM specifications set out in Art. 63.01.

Providing the fuel is within the FIM specifications, a certificate containing a test report and batch number will be issued to the fuel company.

The fuel company shall be able to provide a copy of such certificate to their client rider/teams before they take part in a race.

Contact for fuel analysis: fimfuels@intertek.com.

A list of fuels which are in conformity with FIM specifications will be published by FIM on the FIM website.

Furthermore, in the cases in which only fuel from the appointed supplier is permitted (for a specific event or the entire World Championship, Prize or Cup), the aforementioned fuel shall have been previously tested in a FIM appointed laboratory in order to test its conformity with the FIM specifications as set out in Art. 63.01:

- in case of conformity, a certificate of conformity (including test report and tested batch number) shall be available and Art. 01.63 applies in case of controls for the riders/teams;
- in case the conformity is not achieved, the FMN of the organising country/the Organiser/the Promoter shall ask the FIM for a waiver in order to enable the use of fuel not corresponding to FIM specifications. If the waiver is granted, the riders/teams will be responsible for using the fuel provided without changing its composition. Controls may be carried out by FIM.

63.01 FIM specifications for unleaded fuels or mixtures of unleaded fuels

The following specifications are set for unleaded fuel or the mixture of unleaded fuels:

- a) The following properties shall be within the following thresholds (for each property, the relative test methods to be used for the measurement are indicated):

Property	Units	Min.*	Max.*	Test Method
-----------------	--------------	--------------	--------------	--------------------

RON		95.0	102.0	EN ISO 5164 or ASTM D2699
MON		85.0	90.0	EN ISO 5163 or ASTM D2700
Oxygen (includes 10% ethanol allowance)	% (m/m)		3.7	EN ISO 22854 ¹ or EN 13132 or elemental analysis
Nitrogen	% (m/m)		0.2	ASTM D 4629 ² or ASTM 5762
Benzene	% (V/V)		1.0	EN ISO 22854 or ASTM D6839 or ASTM D5580
Vapour pressure (DVPE)	kPa		100.0	EN 13016-1 or ASTM D5191
Lead	mg/L		5.0	ICP-OES or AAS
Manganese	mg/L		2.0	ICP-OES or AAS
Density at 15°C	kg/m ³	720.0	785.0	EN ISO 12185 or ASTM D4052
Oxidation stability	minutes	360		EN ISO 7536 or ASTM D525
Sulphur	mg/kg		10.0	EN ISO 20846 or ASTM D5453
<u>Distillation:</u>				EN ISO 3405 or ASTM D86
E at 70°C	% (V/V)	20.0	52.0	
E at 100°C	% (V/V)	46.0	72.0	
E at 150°C	% (V/V)	75.0		
Final Boiling Point	°C		210	
Residue	% (V/V)		2.0	
Appearance	clear, bright and visually free from solid matter and undissolved water			Visual inspection
Olefins	% (V/V)		18.0	EN ISO 22854 or ASTM D6839
Aromatics	% (V/V)		35.0	EN ISO 22854 or ASTM D6839
Total diolefins	% (m/m)		1.0	GC-MS or HPLC
<u>Oxygenates:</u>				EN ISO 22854 ¹ or EN 13132
Methanol	% (V/V)		3.0	The only oxygenates permitted are paraffinic mono-alcohols and paraffinic mono-ethers (of 5 or more carbon atoms per molecule) with a final boiling point below 210°C.
Ethanol	% (V/V)		10.0	
Isopropanol	% (V/V)		12.0	
Isobutanol	% (V/V)		15.0	
<i>tert</i> -Butanol	% (V/V)		15.0	
Ethers (C5 or higher)	% (V/V)		22.0	
Others	% (V/V)		15.0	

¹ In cases of dispute EN ISO 22854 will be the reference method.

² In cases of dispute ASTM D 4629 will be the reference method.

*All reported min. and max. thresholds do not include the tolerance, which needs to be calculated in accordance with ISO 4259 and taken into account to correct the min. and max. thresholds.

b) The total of individual hydrocarbon components present at concentrations of less than 5% (m/m) must constitute at least 30% (m/m) of the fuel. The test method will be GC-FID (gas chromatography-flame ionisation detector) and/or GC-MS (gas chromatography-mass spectrometry).

c) The total concentration of naphthenes, olefins and aromatics classified by carbon number must not exceed the values given in the following table:

% (m/m)	C4	C5	C6	C7	C8	C9+
Naphthenes	0	5	10	10	10	10
Olefins	5	20	20	15	10	10
Aromatics	-	-	1.2	35	35	30

Bicyclic and polycyclic olefins are not permitted. The fuel must contain no substances which are capable of exothermic reaction in absence of external oxygen.

63.02 FIM specifications for mixtures of unleaded fuel(s) and lubricant

The lubricant

- must not change the composition of the fuel fraction when added to the fuel;
- must not contain any nitro-compounds, peroxides or any other engine power boosting additives;
- must in no way contribute to an improvement in overall performance;
- during the distillation up to 250°C, must not show a reduction in mass by evaporation of more than 10% (m/m) (test method: simulated distillation GC);
- must contain a max. content of anti-knock agents (lead, manganese, iron) of 10 mg/Kg (test method: ICP-OES).

Moreover, the following specifications are set for the mixture of unleaded fuel(s) and lubricant:

a) The following properties shall be within the following thresholds (for each property, the relative test methods to be used for the measurement are indicated):

Property	Unit	Min.	Max.	Test Method
RON			102.0*	EN ISO 5164 or ASTM D2699
MON			90.0*	EN ISO 5163 or ASTM D2700
Density at 15°C	kg/m ³	690**	815**	EN ISO 12185 or

				ASTM D4052
--	--	--	--	------------

*Reported min. and max. thresholds do not include the tolerance, which needs to be calculated in accordance with ISO 4259 and taken into account to correct the min. and max. thresholds.

** Min. and max. thresholds do include the tolerance.

63.03 Air

Only ambient air may be mixed with the fuel as an oxidant.

63.05 Sampling and Testing

The FIM may require fuel controls, i.e. controls of the unleaded fuel, mixture of unleaded fuels or mixture of unleaded fuel and lubricant, used by riders/teams at events. These controls involve an initial sampling at the event and further testing in the FIM appointed laboratory.

63.05.01 Sampling

- 1) The FIM Technical Director (or the FMNR Chief Technical Steward when there is no FIM Technical Director appointed) is the sole official responsible for the sampling management and supervision.
- 2) Riders/teams selected for fuel controls are directed to proceed with their vehicles to the area that has been designated for this purpose.
- 3) The FIM Technical Director/FMNR Chief Technical Steward collects the fuel from the motorcycle by using only new sample containers and pipettes/hand pumps.
The fuel is transferred through the use of the pipette/hand pump directly from the fuel tank into three containers, denominated A, B and C. The containers are closed and sealed by the FIM Technical Director/FMNR Chief Technical Steward.
- 4) The FIM Technical Director/FMNR Chief Technical Steward fills in (in all its parts) and signs the Fuel Sample Declaration Form (see 63.04.03). The rider or a team representative also signs this Form, after verifying that all the information is correct.
- 5) The FIM Technical Director/FMNR Chief Technical Steward prepares an appropriate shipping box containing the collected A, B and C samples and a copy of the respective, signed, Fuel Sample Declaration Form. The box is then shipped to the FIM appointed laboratory by registered courier.

63.05.02 Testing

- 1) One or more properties to be checked (following the relevant testing method as per Art. 63.01 and 63.02) are set by the FIM for each selected rider/team.

- 2) Sample A is the first sample to be tested by the FIM appointed laboratory.
- 3) Sample B can be used for a second analysis if required by the FIM. The test result of the A or B sample more favourable to the rider/team is taken into account. Costs for the shipping and testing of sample A and B are paid by FIM.
- 4) As soon as possible after completing the testing, the FIM appointed laboratory reports the test results directly to the responsible CTI Coordinator.
- 5) For negative cases (i.e. conformity of the tested property(ies) with the specification), the riders/teams concerned will be individually informed by the FIM in due course, copying the rider/team's FMN, the FIM Technical Director/FMNR Chief Technical Steward, the competent authority (e.g. Race Direction, International Jury), the CTI Director, the Director and Coordinator(s) of the sporting Commission concerned.
- 6) Only for positive cases following testing of sample A or B or A and B (i.e. non-conformity of one or more properties*), the responsible CTI Coordinator notifies by electronic mail* the rider/team concerned (including the testing results) and, 24 hours after, forwards the relevant information to the rider/team's FMN, the FIM Technical Director/FMNR Chief Technical Steward, the competent authority (e.g. Race Direction, International Jury), the CTI Director, the Director and Coordinator(s) of the sporting Commission concerned.
 *Note: The non-conformity of one property (except the Appearance) is sufficient for declaring non-conformity of the fuel or the mixture.
- 7) If the rider/team wishes to request a counter-expertise, he must notify the responsible CTI Coordinator by electronic mail* accordingly, within 72 hours of receipt by the FIM of the delivery status notification pertaining to the notification of the test results to the rider/team.
 - If a counter-expertise is requested, the sample dedicated to the counter-expertise is sample C and the test shall aim at checking the same property(ies) previously checked on sample A/B. The rider/team can request that sample C be tested at one of the available FIM appointed laboratories. Costs for shipping and testing of sample C are paid by the rider/team concerned.
 Upon notification of the sample C results, the responsible CTI Coordinator notifies by electronic mail* the rider/team concerned (including the testing results) and forwards the relevant information to the rider/team's FMN, the FIM Technical Director/FMNR Chief Technical Steward, the competent authority (e.g. Race Direction, International Jury), the CTI Director, the Director and Coordinator(s) of the sporting Commission concerned.
 - If no counter-expertise is requested within the time limit, the responsible CTI Coordinator forwards the relevant information by electronic mail*

the rider/team's FMN, the FIM Technical Director/FMNR Chief Technical Steward), the competent authority (e.g. Race Direction, International Jury), the CTI Director, Director and Coordinator(s) of the sporting Commission concerned.

- 8) The competent authority of the event concerned (e.g. Race Direction, International Jury) takes a decision based on the information received. The Coordinator of the sporting Commission concerned notifies the rider/team concerned regarding the decision by electronic mail*.

The non-conformity of

- A sample (in the cases B sample was not used) or
- B sample (in the cases A sample result was not conclusive) or
- A and B samples or
- A and B and C samples (in the cases B sample was used and a counter-expertise was requested) or
- A and C samples (in the cases B sample was not used and a counter-expertise was requested),

automatically results in the disqualification of the rider/team from the entire event.


No disqualification will be applied in case of conformity of sample C.

Furthermore, in any case, other penalties may be applied.

- 9) The rider/team has the right to appeal against the decision of competent authority of the event concerned (e.g. Race Direction, International Jury) in accordance with FIM Disciplinary and Arbitration Code applicable to the relevant discipline.

*The receipt of a delivery status notification will be deemed as proof of delivery.

63.05.03 Fuel Sample Declaration Form

 FIM WORLD CHAMPIONSHIPS, CUPS AND PRIZE EVENTS Fuel Sample Declaration Form									
Discipline									
IMN (xxx/xx)									
Rider/team's name									
Rider/team's number									
Rider/team's email or telephone number									
Team									
Vehicle's make									
Fuel's make and type									
Fuel origin (public station or race supplier)									
Fuel samples taken on date (dd/mm/yy)									
Fuel samples taken at (right before or right after): MOTOCROSS TRIAL TRACK RACING ENDURO/ISDE RALLIES/BAJAS <input type="checkbox"/> Practice <input type="checkbox"/> Day 1 <input type="checkbox"/> Heat n°__ <input type="checkbox"/> Day 1 <input type="checkbox"/> Day 1 <input type="checkbox"/> Qualifying race <input type="checkbox"/> Day 2 <input type="checkbox"/> Day 2 <input type="checkbox"/> Day 2 <input type="checkbox"/> Race 1 <input type="checkbox"/> Day n°__ <input type="checkbox"/> Day n°__ <input type="checkbox"/> Race 2									
	<table border="1"> <thead> <tr> <th></th> <th>Container seal n°</th> </tr> </thead> <tbody> <tr> <td>Sample A</td> <td></td> </tr> <tr> <td>Sample B</td> <td></td> </tr> <tr> <td>Sample C</td> <td></td> </tr> </tbody> </table>		Container seal n°	Sample A		Sample B		Sample C	
	Container seal n°								
Sample A									
Sample B									
Sample C									
The above listed details refer to Fuel samples taken from the Fuel tank of the motorcycle specified. Sample A is the first testing sample to be used by the FIM appointed laboratory. Sample B can be used for a second analysis if required by the FIM. Sample C is used if a counter-expertise is required by the rider/team. The serial numbers of the vial seals and the accuracy of the listed information have been verified.									
Rider or team responsible name									
Rider or team responsible signature									
FIM Technical Director/FMNR Chief Technical Steward name									
FIM Technical Director/FMNR Chief Technical Steward signature									

01.65 EQUIPMENT AND PROTECTIVE CLOTHING DURING PRACTICE AND RACE

The FIM cannot be held liable for any injuries that a rider or passenger may sustain from the use of a specific item of equipment or protective clothing.

65.01 Clothing and protectors

It is compulsory that riders/passengers wear either a suit or trousers and long-sleeve shirt.

It is recommended to use suit, trousers, long-sleeve shirts and undergarments made of textiles which are not fully constituted of nylon or spandex (e.g. Lycra, Elastan), in order to avoid degradation in case of abrasion (friction).

Moreover, it is compulsory that riders/passengers wear back and chest protectors. It is recommended that back and chest protectors comply with EN 1621-2 and prEN 1621-3 (or EN 14021), respectively.

Repaired overalls are acceptable provided that the repair guarantees protection to the same standard as the original garment. The Chief Technical Steward has the right to refuse any temporary repairs which are not deemed to provide the same protection as the original garment.

65.02 Footwear

Footwear, in a good condition, made of leather or other materials having equivalent properties, shall be worn and have a minimum height of 30 cm.

65.03 Gloves

Riders/passengers shall wear gloves made of leather or other materials having equivalent properties.

65.04 Eye protection

Riders/passengers shall wear goggles. The use of glasses, helmet visors and "roll offs" is also permitted. The use of "tear offs" is forbidden for environmental reasons. The material used for glasses, goggles and visors must be made of shatter-proof material. Helmet visors must not be an integral part of the helmet.

Eye protectors which cause visual disturbance (e.g. scratched) must not be used.

01.67 WEARING OF HELMETS

- It is compulsory for all participants taking part in practice and races to wear a protective helmet. The helmet must be properly fastened, be of a good fit, and

be in good condition. The helmet must have a chin strap type 'retention system'.

- A protective lower face cover must be present and must be not detachable and not moveable.
- Helmets constructed with an outer shell made of more than one piece are not permitted (e.g. they must not contain any seam).
- A retention system with a strap and the double D ring closing system is recommended.
- All helmets must be marked with one of the official international standard marks mentioned in Art. 01.70. Any FMN approval marks do not substitute the official international standard marks.
- A helmet is made to provide protection. A helmet is not a platform to attach foreign objects. Cameras or other accessories are NOT permitted nor shall be attached to the rider's helmet.
- Long hair must not come out of the helmet. Long hair must be completely contained within the helmet.

Failure to observe the above rules will entail exclusion.

01.69 HELMET OPERATIVE INSTRUCTIONS

69.01

Scrutineers, under the supervision of the Chief Technical Steward, may check prior to practice and the races that all helmets meet the technical requirements.

69.02

If a helmet does not meet the technical requirements or is found to be defective, the Technical Steward must clearly mark in red (e.g. with a red dot) all international marks without destroying them and retain the helmet until the end of the event. The rider must submit another helmet for approval by the Technical Steward. After an accident involving impact, the helmet must be presented to the Technical Steward for examination.

69.03

All helmets must be intact and no alteration must have been made to their construction. After an accident involving a shock or impact, the helmet must be presented to the Technical Steward for examination.

69.04

The Chief Technical Steward and/or the Technical Steward may perform the following checks before the rider is permitted to take part in practice of the race:

69.04.1 That the helmet fits well on the rider's head.

69.04.2 That it is not possible to slip the retention system over the chin, when fully fastened.



69.04.3 That it is not possible to pull the helmet over the rider's head by pulling it from the back of the helmet.


01.70 RECOGNISED HELMET APPROVAL MARKS

Helmets must conform to one of the recognised international standards:

EUROPE	ECE 22-05 (only "P" type)
JAPAN	JIS T 8133:2015 (only "Type 2 Full face")
USA	SNELL M 2015

Examples of labels are reported below (for Europe, the country numbers which have granted the approval are also indicated):

EUROPE	 <p>051406/P-1952</p> <p>3/ 1 for Germany, 2 for France, 3 for Italy, 4 for the Netherlands, 5 for Sweden, 6 for Belgium, 7 for Hungary, 8 for the Czech Republic, 9 for Spain, 10 for Yugoslavia, 11 for the United Kingdom, 12 for Austria, 13 for Luxembourg, 14 for Switzerland, 15 (vacant), 16 for Norway, 17 for Finland, 18 for Denmark, 19 for Romania, 20 for Poland, 21 for Portugal, 22 for the Russian Federation, 23 for Greece, 24 for Ireland, 25 for Croatia, 26 for Slovenia, 27 for Slovakia, 28 for Belarus, 29 for Estonia, 30 (vacant), 31 for Bosnia and Herzegovina, 32 for Latvia, 33 (vacant), 34 for Bulgaria, 35 (vacant), 36 for Lithuania, 37 for Turkey, 38 (vacant), 39 for Azerbaijan, 40 for The former Yugoslav Republic of Macedonia, 41 (vacant), 42 for the European Community (Approvals are granted by its Member States using their respective ECE symbol), 43 for Japan, 44 (vacant), 45 for Australia, 46 for Ukraine, 47 for South Africa and 48 for New Zealand. Subsequent numbers shall be assigned to other countries in the chronological order in which they ratify or accede to the Agreement Concerning the Adoption of Uniform Technical Prescriptions for Wheeled Vehicles, Equipment and Parts which can be Fitted and/or be Used on Wheeled Vehicles and the Conditions for Reciprocal Recognition of Approvals Granted on the Basis of these Prescriptions, and the numbers thus assigned shall be communicated by the Secretary-General of the United Nations to the Contracting Parties to the Agreement.</p>
JAPAN	 <p>Protective helmet for motor vehicle users T8133:2015 Class 2 Certification No. XX0000000 Label serial No. 0000000000 XXX Manufacturer's name <small>(Trade mark of certification body)</small></p>

USA	 <p>The image shows a SNELL M2015 helmet certification label. It features a warning symbol on the left, a barcode in the center, and the SNELL Memorial Foundation logo on the right. Text on the label includes: 'WARNING', 'SOME REASONABLY FORESEEABLE IMPACTS MAY EXCEED THIS HELMET'S CAPABILITY TO PROTECT AGAINST SEVERE INJURY OR DEATH.', 'SAMPLE OF THIS HELMET MODEL HAS PASSED THE SNELL STANDARD AND IS SO CERTIFIED.', and 'SNELL MEMORIAL FOUNDATION'.</p>
-----	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

01.73 NATIONAL COLOURS FOR HELMETS


In competitions between national teams, it is compulsory that the helmet's overall graphics represent the colours of the team's national flag or the colours as mentioned in the table below. The national flag can be replicated in stripes, bands or other patterns.

Andorra	FMA	White with vertical blue, yellow and red bands
Argentina	CAMOD	White with blue horizontal band
Australia	MA	Green and yellow sides, red, white & blue representation of the Australian flag across the top
Austria	OeAMTC	Bright red with a 60 mm wide black band and the label of the OeAMTC in a white field on the front side
Belgium	FMB	Yellow
Brazil	CBM	Yellow and green
Bulgaria	BMF	Green and red
Canada	CMA	White and 3 Red Maple leaves, one on front and one on each side
Chile	FMC	Red with blue band and yellow stars
China	CMSA	Red and yellow
Czech Republic	ACCR	Blue with red, white and blue border
Denmark	DMU	Red and white
Finland	SML	White with blue cross
France	FFM	Blue
Germany	DMSB	White with black border
Great Britain	ACU	Green
Greece	ELPA	White with blue border
Hungary	MAMS	Red and green
Ireland	MCUI	Green and orange
Italy	FMI	Red with one green and one white horizontal band
Japan	MFJ	White with red circle on top
Kenya	KMSF	Black, Red, Green, with white bands and the country name KENYA on both sides.
Luxembourg	MUL	Purple
Mexico	FMM	White with green and red border
Monaco	MCM	Blue and white
Netherlands	KNMV	Orange
New Zealand	MNZ	White with black kiwi on front

Norway	NMF	Red and blue
Peru	FPEM	Red with 75 mm wide white strips and blue and yellow chequered border
Poland	PZM	White with red band
Portugal	FNM	White
Rumania	FRM	Black with vertical blue, yellow and red bands with national emblem.
Russia	MFR	White with a red border and a vertical red band with star
San Marino	FSM	White with the San Marino National emblem
Slovakia	SMF	Blue, red and white
South Africa	MSA	Black, green, blue and red with yellow and white bands
Spain	RFME	Yellow and red
Sweden	SVEMO	Blue and yellow
Switzerland	FMS	Red with white cross
Uruguay	FUM	Light blue
USA	AMA	Blue with 2 white bands

In addition, the defending FIM Team World Champion is allowed to wear the rainbow colours on the helmet.

The rider's personal sponsors may be part of the overall graphics or displayed in a separate and dedicated area below the goggles strap (usually horizontal). The helmet model of each of the riders of a team may be different, but the graphics must have a similar visual appearance.



The overall graphics on the helmet must always be approved, in any case, by the FMN of the team.

Whenever a team is using a helmet and there is a case of *force majeure* (e.g. change of rider, broken helmet, etc.), the helmet in question can be replaced by any other helmet, provided that it complies with the FIM Technical Rules for the current year and has been presented to the Technical Stewards of the event.

01.75 BADGE OF THE FIM

Under certain circumstances the FIM may permit the use of the FIM badge on certain equipment in order to show that the latter conforms to the standards laid down by the FIM. When this authorisation is granted and provided the equipment on which it appears is in good condition, the badge is then the guarantee of the conformity with the standard set by the FIM.

01.76 NUMBER SASHES (BIBS)

The starting number on the rider's bib or vest must be the same as on his motorcycle.

Starting numbers must be in conformity with the following specifications:

76.01

Black numbers on a white background must be used.

76.02

The size of the area in which numbers are printed is: 25 x 25 cm maximum.

76.03

Height of number: 15 cm.

76.04

Width of number: 6 cm.

76.05

Width of stroke: 2 cm.

76.06

Only the space outside the 25 x 25 cm area may be used for publicity.

76.07

Bibs manufactured from PLASTIC material are not allowed.

01.77 TECHNICAL VERIFICATIONS

77.01 Preparation

- Prior to the Technical Verifications, it should be decided who is doing what and note decisions. "Efficiency" must be the watchword. Always keep cheerful and remember the reasons for scrutineering: SAFETY AND FAIRNESS.
- Before the START of the competition, a closed and guarded area (closed parc/parc-fermé) shall be prepared.
- Inspection must take place under cover with a large enough area.
- Inspection area must be supplied with the necessary equipment, including tables, chairs, electric light and power outlet.
- Weighing apparatus must be accurate, practical and have a minimum resolution of 100g. Weighing scales must have been certified by a National Institute within the period of 24 months before the event. Certified master weights and their certificate must be available for verifying.
- The necessary tools are listed below:
 - ✓ Revolution meter
 - ✓ Sound meter, calibrator and spare batteries
 - ✓ Slide calliper (for verifying engine capacity, carburettor diameter, etc.)
 - ✓ Depth gauge
 - ✓ Steel measuring tape
 - ✓ Arrangement for measuring ground clearance (for Sidecars)
 - ✓ Seals
 - ✓ Weighing apparatus (to be furnished by the Organiser) (and set of reference weights)
 - ✓ Tools for measuring the engine capacity
 - ✓ Lampoil tester is recommended and when used, it indicates the cylinder capacity. When a more precise measurement is required, the Chief Technical Steward may ask to take the cylinder head off the cylinder.
 - ✓ Colour for marking parts
 - ✓ Heat resistant stickers or paint for marking the silencer (and solvent)
 - ✓ Magnet
 - ✓ Adequate fuel sample bottles
 - ✓ PC with CD Drive + updated operating system
 - ✓ Printer, etc. are recommended
 - ✓ Calculator
- The necessary documents are listed below:
 - ✓ Supplementary Regulations
 - ✓ FIM Technical Rules - current year
 - ✓ FIM Rules of the discipline concerned
 - ✓ FIM Sporting Code
 - ✓ Homologation papers (if applicable)
 - ✓ Writing material

✓ Technical Verifications forms

- All necessary measures and administrative equipment should be in place at least 1/2 hour before the start of the Technical Verifications is due to open (time in Supplementary Regulations).

77.02 Verifications

- The Technical Verifications must be carried out in conformity with the procedure and times fixed in the CEN Rules and the Supplementary Regulations of the event.
- The Sound control must be carried out first. The Sound level will be recorded in the technical card. The exhaust silencer will be marked with paint or sticker.
- An example of minimum verifications that shall be performed is given below:

INITIAL TECHNICAL VERIFICATIONS	TRIAL	MOTO CROSS	TRACK RACING	ENDURO	CROSS-COUNTRY RALLIES and BAJAS
Make + model	✓	✓	✓	✓	✓
Sound	✓	✓	✓	✓	✓
Cut-off switch	✓	✓	✓	✓	✓
Self-closing throttle	✓	✓	✓	✓	✓
Lights (front, rear, brake)	✓*			✓*	✓
Race fuel certificate	✓	✓	✓	✓	✓
Vehicle identification plate/chassis number				✓	✓
Crankcase				☐	☐
Wheels (hubs)				☐	☐
Registration plate + insurance (green card)				✓	✓
Weight + ballast	✓	✓	✓		
Fuel tank	✓				✓
Silencer	✓	✓	✓	✓	✓
Carburettor			✓		

Guard for the countershaft sprocket and rear sprocket	✓	✓	✓	✓	✓
Handlebar ends + protection + levers	✓	✓	✓	✓	✓
Front/rear brake disc protection	✓				
Side stand				✓**	✓
Tyres	✓	✓	✓	✓	✓
Helmet(s) + national colors	✓	✓	✓	✓	✓
Protective clothing	✓	✓	✓	✓	✓

* not applicable for closed circuits when specified in the Supplementary Regulations

** not applicable in SuperEnduro

- An overall inspection of the motorcycle must be carried out in conformity with the FIM rules. On accepted motorcycles a sticker or paint will be applied on the front of the main frame, in conformity with Arts. 082.8.2.1 of the Cross-country rallies Appendices.
- The Technical Verifications will only be carried out when the Technical Verifications form of the motorcycle has been presented by the rider or his mechanic.
- The fuel tank shall contain a minimum amount of fuel for the sound control.
- At the arrival, at the end of the competition, all the marked parts on the motorcycles must be controlled. After control, the machines must be placed in a closed park for 30 minutes after arrival of the last rider from the class concerned, in case a protest is lodged or further examination is required.
- If a motorcycle or a part of a motorcycle has to be verified and completely dismantled, the motorcycle, the part or the group of parts must be sealed and shipped to a place where the required tools are present for a disassembly. The Clerk of the Course/FIM Race Director must take the decision for this operation.
- The disassembly and the verification of the motorcycle or the parts in question must take place in the presence of the Technical Steward, appointed to the event.

- The Organiser will pay the costs for the transportation and for the verification according to Art. 77.02.14 and 77.02.15.
- If a disassembly is required and ordered by the Clerk of the Course/FIM Race Director, following a protest, according to Art. 77.02.14 and 77.02.15, the losing party will incur all the transportation and verification costs, or a part of these costs fixed by the Clerk of the Course/FIM Race Director.

77.03 FMNR Chief Technical Steward and technical stewards

- The Chief Technical Steward must be in attendance at an event one hour before the Technical Verifications are due to begin. He must inform the Clerk of the Course/FIM Race Director and FIM Technical Director, if present, of his arrival.
- The Chief Technical Steward must ensure that all technical stewards appointed for the event carry out their duties in a proper manner. The Chief Technical Steward shall appoint the technical stewards to individual posts for the race, practices and final control.
- Scrutineers can have different tasks, but the team of scrutineers must have a minimum of four persons. The FMNR Chief Technical Steward must be a holder of an FIM SENIOR Technical Stewards Licence and at least one Technical Steward must hold a FIM Technical Stewards Licence. A minimum number of scrutineers is required according to the following:
 - Sound test, silencer marking: two
 - Machine inspection, helmet and clothing: two
 It is recommended to have 2 up to 4 helpers (staff).
- The Sound Control Officer (SCO) must be holder of a valid FIM Technical Steward's license, come with good knowledge and experience of the sound control and application of the test method. The FMNR may propose the services from a special technician (acoustic engineer) if there is no FIM licenced Technical Steward available to act as SCO.
- After the Technical Verifications has been completed the Chief Technical Steward will submit to the Clerk of the Course/FIM Race Direction a list stating the names of the accepted riders, machines and the sound levels.
- During the event, in the arrival and departure areas, the technical steward must control the repairs and changes made to the machines. He must control that no outside assistance is made. He must also control the condition of the machines.
- At individual time checks, the technical steward must control repairs and other technical assistance. He must also control that the machines are marked in order to ensure that no change in motorcycle occurred on the course.

- At the arrival, at the end of each day, the technical steward must check all parts and the condition of the machine. A rider is allowed an extra 30 minutes to repair or replace a silencer and/or exhaust pipe only.
- If a motorcycle is involved in an accident, the Technical Steward must check the machine to ensure that no defect of a serious nature has occurred. However, it is the responsibility of the rider to present his machine for this re-examination together with the helmet and clothing worn.
- The Chief Technical Steward has the right to look/ inspect any part of the motorcycle at any time of the event.
- All technical stewards shall be well informed and shall make sure their FMN has supplied them with all technical "updates" that may have been issued subsequent to the printing of the Technical Rules books.

77.04 FIM Technical Director

- The FIM Technical Director is appointed by the Director of the FIM International Technical Commission in consultation with the Director of the FIM Cross-Country Rallies Commission.
- The FIM Technical Director is not responsible for the technical verifications but will ensure that they are carried out in accordance with the FIM Technical Rules.
- The FIM Technical Director works in cooperation with the FIM Race Director and the FIM Delegate.
- The authority and duties of the FIM Technical Director include but are not limited to (Please, also refer to the FIM Technical Rules):
 - a) The FIM Technical Director will report any concerns or deficiencies relating to the technical verifications to the FIM Race Director and FIM Delegate and present proposals to resolve such concerns.
 - b) The FIM Technical Director is the final arbiter in relation to technical issues at the event.
 - c) The FIM Technical Director will examine with the Chief Technical Steward the motorcycle(s) and the protective equipment of any rider(s) involved in serious or fatal accidents and present a written report to the FIM Delegate.
 - d) The FIM Technical Director will attend all meetings of the Race Direction, but without voting rights.

77.05 Rider and/or mechanic

- The rider and/or the mechanic and/or the Team Manager must attend at least once the Technical Verifications with the (rider's) machine within the time limits stated in the Supplementary Regulations.
- On request of the technical steward, the rider must present themselves to the Technical Verifications.
- The maximum number of persons present at the technical verifications will be the rider and/or the mechanic and/or the Team Manager.
- A rider remains at all times responsible that his machine and his personal protective gear are in conformity with the FIM Cross-country rallies Technical Rules.
- The rider and/or the mechanic and/or the Team Manager must present a clean motorcycle in conformity to the FIM Cross-country rallies Technical Rules and a duly filled in and confirmed Technical Verification form.
- A rider and/or the mechanic and/or the Team Manager must present one motorcycle only.
- The rider and/or the mechanic and/or the Team Manager must present the rider's protective wear (equipment), e.g. helmet and clothing.
- Riders/mechanics/Team Managers must confirm their agreement by signing the register. The motorcycles will then be placed in a closed park.
- Competitors must retrieve their machines within 30 minutes after the opening of the closed park area, except for the machines that are chosen for disassembly. After this time limit, the closed park officials will no longer be responsible for the machines left behind.
- Any rider failing to report as required by the provisions below may be excluded from the meeting.
- The Clerk of the Course/FIM Race Director may prohibit any person who does not comply with the rules, or any rider who could be a danger to other participants or to spectators, from taking part in the competitions.

01.78 DANGEROUS MACHINES

If, during practice or the race, a Technical Steward finds that a machine is defective and might constitute a danger to other riders, he must immediately notify the Clerk of the Course/FIM Race Director or his deputy. It is their duty to exclude such a machine either from the practice or from the race itself.

01.79 SOUND CONTROL

NOTES:

- EPVs (Group J) are exempted from sound level control.
- All motorcycles must be checked for sound level during the Technical Verifications.

In order to pursue the measures taken to reduce the sound level in favour of environment and in the framework of the 'RIDE QUIET' campaign, a new method for measuring the sound level called "2 metre max" is applied as from 2013 in all 'all-terrain' disciplines.

The technical specifications and the resources to apply such a method, for the use of the technical stewards and officials, are outlined in the present Article.

The "2 metre max" method shows a very good correlation between the sound power level (L_{WA}) issued by motorcycles in full acceleration, and the maximum sound pressure levels measured at proximity of the same motorcycles, with engines at idle and quickly taken to their maximum rotational speeds.

The "2 metre max" method will consist in quantifying not only the sound level produced by the silencer of the exhaust, but the maximum global sound level achieved by the motorcycle when the engine rpm's are raised to the maximum engine speed, limited by a natural regulation (for 2 strokes) or rev limiters (for 4 strokes).

Only the sound levels measured with the "2 meter max" method will be considered by the technical stewards and by the Race Direction/Jury of the event to decide whether the motorcycle is in conformity with the maximum sound levels authorised.

79.01 Preparation of the sound meter

For all FIM Championships and Prizes, all sound meters must have a frequency response According to IEC61672 Section 11 within a limit of plus or minus 2 dBA from 125 to 8000 Hz at 94, 104 and 114 dBA.

Sound level measuring equipment must also include:

- a compatible calibrator, which must be used immediately before testing begins and always just prior to a re-test if a disciplinary sanction may be imposed;
- a tachometer.

Two sets of equipment must be available in case of failure of tachometer, sound level meter or calibrator during the Technical Verifications.

The sound meter shall be prepared by applying the following procedure:

- Activate the 'A' weighing
- FAST time weighting must be activated
- Select the highest range available (ex. 80~130 dB)

- Calibrate the sound meter according to the instructions, taking into account the incidence of the wind foam ball
- Position the wind foam ball on the microphone
- Activate the function MAX MIN – set on MAX

79.02 Set up of the sound meter and the motorcycle


The sound levels will be measured with the microphone fixed on a tripod at a height of 1.35 m above the ground, in horizontal (levelled) position. It is helpful to have the microphone equipped with an extension cable to the sound meter.

For the place and position of the motorcycle, ensure that there are no solid obstacles within 10 m around the microphone.

Depending on the vehicle, the sound meter will be positioned

- for Solo motorcycles (except for Snowmobiles): at an angle of 45° from the longitudinal axis of the vehicle, on the exhaust side, at a distance of 2 m behind the vehicle (measured from the point where the centre of rear tyre touches the ground).
- for Solo motorcycles with 2 exhaust outputs: at an angle of 45° from the longitudinal axis of the vehicle, on the side of the air intake, at a distance of 2 m behind the vehicle (measured from the point where the centre of rear tyre touches the ground). Note: if a central positioned air intake is used, both sides will be tested.
- for Snowmobiles: at an angle of 90° from the longitudinal axis of the vehicle, on the side of the silencer, at a distance of 2 m next to the vehicle (measured from the silencer exit). For continuity of the measurement, use the handlebar as a reference to line up the machine with the microphone - the exhaust pipe is usually located on the right hand side of the machine and directly under the handlebar position. Note: the use of only one silencer is allowed for Snowmobiles.
- for Sidecars: at an angle of 45° from the longitudinal axis of the vehicle, on the sidecar side, at a distance of 2 m behind the vehicle (measured from the point where the sidecar tyre touches the ground). If the exit of the silencer is closer to the motorcycle rear wheel, the reference point will be the contact point of the motorcycle rear wheel on the ground (as for Solo motorcycles).
- for Quads: at an angle of 45° from the median longitudinal axis of the vehicle, at a distance of 2 m behind the vehicle (measured from the point where the line drawn perpendicular to the rear axle touches the ground).
- for Quads with the exhaust moved out of the median axis: at an angle of 45° from the exhaust axis, on the offset side, at a distance of 2 m behind the


vehicle (measured from the point where the line drawn perpendicular to the rear axle touches the ground).



The sound level for engines with more than one silencer will be measured on each exhaust end.

Silencers fitted with adapters aiming to reduce the sound level shall be permanently fitted.

To make repetitive measurements, all motorcycles can be positioned into a small frame fixed on the ground, making sure to respect the 45° requirements. A squared frame helps the positioning of the motorcycle.



Vehicles which are not equipped with a gear box neutral must be placed on a stand.

It is preferred to make the tests on soft ground, not reverberating, i.e. grass or fine gravel.

In other than moderate wind, machines should face forward against the wind direction.

The ambient sound at the point of measurement must be minimum 15 dBA less than the lowest FIM sound limit applied in each discipline.

It is recommended to regularly re-calibrate the sound meter during the test day.

79.03 The test procedure

A technical steward (nominated as Sound Control Officer, "SCO", see 77.03) takes place next to the vehicle, opposite to the sound meter/microphone, in order not to screen or stand between the bike and the microphone.

The Sound Control Officer (SCO) must have arrived in sufficient time for discussions with the Clerk of the Course/FIM Race Director and other Technical Officials in order that a suitable test site and testing procedure can be agreed.

A second technical steward can be present to help. The rider can also be present.


It is strongly advised that the technical steward(s) use earplugs, a headset or ear protectors.

The measurement is made with motorcycle on its wheels, with a hot engine. During the sound test, only the rider may sit on the vehicle in the normal riding position.

A rider or a mechanic, placed on the left side of the motorcycle, shall disengage the clutch.

The SCO (and not others) shall open the throttle as fast as possible (instantly, within 0.3 s) until "full open throttle", in order to reach the maximum rpm value ("max. rpm").

- For Motocross, Enduro/SuperEnduro, Cross-country rallies/Bajas and Track Racing motorcycles with no FIM homologated silencers, the "max rpm" is the one defined by the ECU (for 4-stroke engines), or by a natural regulation (for 2-stroke engines).
When in doubt, it can be verified that such "max. rpm" value is higher than the rpm value at which the vehicle supplies its maximum power (kW) ("max. power rpm").



- For Trial, the "max rpm" is established at 10000 (± 200) rpm and obtained thanks to a dedicated "sound test" mapping of the internal ECU or an external one, purpose-made and connected in occasion of the test.
- For Track-Racing with FIM homologated silencers, when sound tests are needed, the "max rpm" is established at 11000 (± 500) rpm.

The SCO then keeps the engine at the "max. rpm" value for at least 1 s (or until there is an audible sign of over-revving the engine), during which the measurement is taken.

To conclude the test, the SCO releases the throttle quickly. The maximum noise value (dB/A) registered during the measurement interval is then read on the sound meter and recorded. This noise value shall not be rounded down to the nearest whole number.

The noise value is then compared with the sound limits (see Art. 79.04).

The noise test can be "PASSED" or "NOT PASSED":

- "PASSED": The sound test is considered "passed" if the recorded noise value is below or equal to the sound limits of Art. 79.04. The silencer can then be marked by the SCO at the end of the test.

The silencer shall not be changed after verification.

The end opening of the silencer shall remain unmodified once it has been checked and marked.


- "NOT PASSED": The sound test is considered "not passed" if the recorded noise value is above the sound limits of Art. 79.04. In this case, the vehicle (with the same silencer) can be presented again, but for two more tests maximum. If the third test result is negative, the rider
 - can present a different or repaired silencer (in case the sound test was done before the race)
 - will receive a penalty (in case the sound test was done during or after the race).

The sound meter is then reset by pushing on the side-line and armed by pushing on the side-line again.

Notes:

- If the engine starts to misfire, close the throttle slightly and re-open the throttle.
- If detonations appear, the measurement must be started again.
- For vehicles without an engine rev. limiter, the throttle will have to be opened not more than 2 s or until there is an audible sign of over-revving the engine.
- Even in case a vehicle has not exceeded the respective sound limit, if there is any doubt, the vehicle may be checked again.
- If the vehicle is unable to reach the "max. power rpm" value, the vehicle shall be refused. Any attempt by a participant to prevent his engine from reaching the "max. power rpm" will be considered a breach of the rules.

- In case the SCO doubts that the "max. power rpm" value (as declared by the manufacturers or previously obtained with the dyno test), he/she shall measure the engine speed with a tachometer connected to the spark.



1. The Inspector shall open the throttle until full open throttle within 0.3 seconds.
2. And keep at the max rpm (at rpm limiter) at least 1 second. Then, release the throttle quickly.
3. The sound level is measured in the all period and the maximum level shall be recorded in any case. (automatically by the sound meter).

79.04 Sound limits

CROSS-COUNTRY RALLIES World Championship	
Maximum Sound limit	
Before race	During or after race
117.0 dB/A (114 as of 2021)	118.0 dB/A (115 as of 2021)

NOTES:

- The values that have to be respected after the race take into account the degradation of the silencer (i.e. the limit is raised of 1 dB/A).
- The values already take into account the accuracy of the method.
- No deductions for ambient temperature, pressure or altitude are allowed.
- The measured noise value shall not be rounded down to the nearest whole number.

79.06

Action and decisions will depend on the Sporting Discipline concerned, and decisions taken during prior discussions with the FIM Technical Director and/or the Chief Technical Steward.

Technical Rules SSV's

Règlement Technique SSV

Table of contents

01.80	DEFINITION.....	61
01.81	REQUIREMENTS	61
01.82	FUEL TANK	62
01.83	CHASSIS	63
01.84	SAFETY CAGE	63
01.85	SEATS	64
01.86	SEAT HARNESSSES.....	65
01.87	BODYPANEL	67
01.88	INTERIOR.....	68
01.89	TRANSMISSION.....	69
01.90	MINIMUM WEIGHT	71
01.91	ENGINE	71
01.92	ELECTRICAL EQUIPMENT.....	73
01.93	SUSPENSION.....	75
01.94	WHEELS	75
01.95	BRAKING SYSTEM	77
01.96	STEERING.....	77
01.97	FIRE EXTINGUISHERS.....	78
01.98	LIGHTS	80
01.99	PILOT EQUIPMENT	80

01.80 DEFINITION

SSV (Side-by-Side Vehicle) are motor vehicles propelled by a single thermal engine, four wheels, two- or four-wheel driven (designated 4X2 or 4X4), produced in series, (minimum 100 units), equipped with a steering system and a steering wheel, controlled by the rider. The seat of the driver and the passenger are positioned 'side-by-side'.

SSV's must be originally designed for 1-, 2- or 4- passengers and fitted with all the equipment required in the international convention on public road circulation. These vehicles must have a circulation insurance and a registration plate approved by the local Institute of Mobility and Transport (IMT) as a quadricycle, T1, T2, T3, or equivalent entity in the case of vehicles registered abroad.

Original part(s): A part which has undergone all the stages of production foreseen and carried out by the manufacturer of the vehicle concerned, and originally fitted on the production vehicle.

01.81 REQUIREMENTS

81.01 Fuel tanks

Any tank containing oil or fuel must be situated in the main structure of the vehicle (position of the fuel tank: see article 82.05).

If the OEM fuel tank is kept, no changes are necessary. If an additional tank is mounted that tank must comply with this regulations.

81.02 Materials

Unless explicitly authorised by the present regulations, the use of the following materials is prohibited unless it corresponds exactly to the material used in the same components of the production vehicle:

- Titanium alloy
- Magnesium alloy
- Ceramics
- Composite

The use of composite material is authorised for the following elements:

- Air filter box
- Air ducts for cooling (cockpit and boot / radiators / intercooler / engine ancillaries / brakes)
- Windscreen lower trim
- Door trims
- Seats
- Supports and fixings fitted inside the cockpit (except seat brackets) and inside the rear boot
- Protection covers fitted inside cockpit and inside rear boot
- Driver and co-driver foot rest
- Console / support for switches
- Bodypanel protections (side, floor, wheel arch)
- Leak-proof box for fuel tank
- Underbody protections
- Additional headlights housings and fairings
- Supports and fixings fitted inside the engine compartment (except engine supports / transmission supports)

- Fuel tank internals
- Electric connecting box

81.04 Screws, nuts and bolts

Unless otherwise stated, all threaded fasteners must be manufactured from iron-based alloys or aluminium-based alloys.

81.05 Maximum speed

130 km/h

01.82 FUEL TANK

The fuel tank must be road legal or homologated for competition.

82.01 Number of fuel tanks

Maximum number of fuel tanks: 2

82.02 Fuel tanks capacity

Maximum combined capacity of the fuel tanks is 130 litres

82.03 Fuel tanks shielding

All vehicles must have shielding (aluminium alloy or steel plate of 6 mm minimum thickness) fitted directly onto the chassis underneath any part of the tank(s) situated less than 200 mm above the plane defined by the lower face of the lowest tubes of the chassis that are situated within the vertical projection of the fuel tank (reference plane).

82.04 Fuel tanks housing

The soft tanks must be contained in a leak-proof housing securely attached to the chassis/safety cage, the minimum specifications of which are as follows:

- Sandwich construction "Glass Reinforced Plastic + Kevlar or Carbon + Kevlar with an intermediate layer of absorbent material" with a minimum wall thickness of 10 mm
- Aluminium alloy with a minimum wall thickness of 3 mm except for the areas for mounting to the chassis.

A leak-proof cover, made from non-flammable material, easily accessible and removable only with the use of tools, must be installed in the protection for tanks, in order to allow the checking of the validity expiry date.

No part of this housing may be situated less than 40 mm above the lower face of the lowest tubes of the chassis that are situated within the vertical projection of the fuel tank.

The housing must not be:

- Longitudinally less than 800 mm rearward of the front axle centreline,
- Transversally less than 50 mm (inwards) from the outer part of the main rollbar feet
- Vertically less than 200 mm from any point of the upper part of the main rollbar.

82.05 Fuel tanks position

The fuel tanks may be situated forward of the main rollbar.

Parts ahead of the back of the seats must be situated below the mounting points of the seats to the chassis.

82.06 Fuel tanks filler hole

The fuel tank filler hole must be situated outside the cockpit.

82.07 Fuel tanks outlet

The outlet of the fuel tank breather and hose must be kept away from hot areas. A safety valve must be installed (and remain visible during all the technical scrutineering procedure(s); it must close automatically by gravity in case of a rollover.

The breather hose should be raised to near the upper limit of the chassis and again directed downwards.

82.08 Fuel lines

Fuel hoses must be resistant to fuel and must have a minimum burst pressure of 10 bars at the minimum operating temperature of 80°C.

All fuel lines which feed (or return from) the engine are recommended to be equipped with automatic fuel shut-off valves, positioned directly next to the fuel tank and shall automatically close all pipelines under pressure in the event of a rupture or loss.

82.09 Fuel cooling

The fitting of fuel coolers is authorised on the return circuit to the tank.

01.83 CHASSIS

83.01 Chassis

Only tubular chassis in iron-based alloys are authorised.

83.02 Standard components

The position of the following components must remain unchanged (unless otherwise specified) in relation to the standard vehicle:

- Mounting points of the suspension and shock absorber components
- Engine and its supports
- Transmission parts (gearbox / differentials ...)
- Steering rack
- Pedal box (see article 5.14)

All these components must be interchangeable (without modification) with those of the standard vehicle.

01.84 SAFETY CAGE

The fitting of a safety cage is compulsory. The safety cage must be homologated by a recognised federation for competition with an homologation paper and/or identification plate. **The safety cage must comply with FIM OFF-ROAD ADDITIONAL TECHNICAL REGULATION.**

84.01 Safety cage repair

~~All repairs to a homologated or certified safety cage, damaged after an accident must be carried out by the manufacturer of the cage or with his approval.~~

84.02 Safety cage tubes

~~Tubes must not carry internally fluids or any other item.~~

84.03 Safety cage (co-)driver access

~~The safety cage must not unduly impede the entry or exit of the driver and co-driver.~~

84.04 Around safety cage

Inside the cockpit, the passage of the following elements between the side members of the body panel and the safety cage are forbidden:

- Electric cables
- Lines carrying fluids (except for drinking water and windscreen washer fluid)
- Lines of the fire extinguishing system.

Members may enter into the occupant's space by passing over the dashboard and trimming.

84.05 ~~Safety cage protect padding (move A1.10)~~

~~All tubes of the cage identified on **Figure 1** and all roof reinforcements must be fitted with paddings approved for competition. Each padding must be fixed in such a way that it is not moveable from the tube and.~~




Figure 1

84.06 Driver/Co-driver back protection

The driver/passenger's seat must be protected by an integral portion of the safety cage structure, immediately positioned behind the driver's seat. This portion must be wider than his shoulders and extends above them when they are seated normally with their seat belt fastened.

01.85 SEATS

All the occupants' seats must be homologated for competition.

85.01 Seat attachments


Each seat must be attached to the chassis via at least 4 supports, 2 at the front and 2 at the rear of the seat.

Supports must be attached to the seat and the chassis using bolts with a minimum diameter of 8 mm (quality 8.8 or higher) and counter plates. The seats must have reinforcement at the locations of the fixation.

The minimum thickness of the supports and counter plates is 3 mm for steel and 5 mm for light alloy materials. The minimum longitudinal dimension of each support is 6 cm.

The minimum area of contact between support, shell/chassis and counter plate is 40 cm² for each mounting point.

Each mounting point must be capable of withstanding a force of 15000 [N] applied in any direction. If quick release systems are used, they must be capable of withstanding vertical and horizontal forces of 18'000 [N], applied non-simultaneously.



01.86 SEAT HARNESSES

It is compulsory to use seat harnesses homologated for competition for each occupant.

It is not allowed to mix parts of harnesses. Only complete sets, of proprietary manufacture, may be used.

The harnesses must be replaced after every severe collision, and whenever the webbing is cut, frayed or weakened due to the actions of chemicals or sunlight.

Elastic devices attached to the shoulder straps are forbidden.

Any harness which does not function perfectly must be replaced.

A safety harness must be used in its homologation configuration without any modifications or removal of parts, and in conformity with the manufacturer's instructions.

86.01 Seat harnesses anchored points

It is prohibited for the safety harnesses to be anchored to the seats or their supports. The anchorage points of the series vehicle can be used.

If the installation on the series anchorage points is impossible, new anchorage points must be installed on the chassis, a separate one for each strap the furthest rearward as possible for the shoulder straps.

Care must be taken that the straps cannot be damaged through chafing against sharp edges.

The recommended geometrical locations of the anchorage points are shown in Drawing below.




Figure 2

In the downwards direction, the shoulder straps must be directed towards the rear, and must be installed in such a way that they do not make an angle of more than 45° to the horizontal

from the upper rim of the backrest, although it is recommended that this angle does not exceed 10°.

The maximum angles in relation to the centreline of the seat are 20° divergent or convergent (measurement in horizontal projection).

Anchorage points creating a higher angle to the horizontal must not be used.

If mounting on the series anchorages is impossible, the shoulder straps may be fixed or leaning on a rear transverse tube fixed to the cage or to the top anchorage points of the front belts.

The shoulder straps may also be fixed to the safety cage or to a reinforcement bar by means of a loop, and may also be fixed to the top anchorage points of the rear belts, or be fixed or leaning on a transverse reinforcement welded between the backstays of the cage (see **Figure 3**) or on transverse tubular reinforcements.




Figure 3 : Mounting holes for harnesses

In this case, the use of a transverse reinforcement is subject to the following conditions:

- The transverse reinforcement must be a tube measuring at least 38 mm x 2.5 mm or 40 mm x 2 mm, made from cold drawn seamless carbon steel, with a minimum tensile strength of 350 N/mm²
- The height of this reinforcement must be such that the shoulder straps, towards the rear, are directed downwards with an angle of between 10° and 45° to the horizontal from the rim of the backrest, an angle of 10° being recommended.
- The lap and crotch straps must not pass over the sides of the seat but through the seat, in order to wrap and hold the pelvic region over the greatest possible surface.
- The lap straps must fit tightly in the bend between the pelvic crest and the upper thigh. Under no conditions must they be worn over the region of the abdomen
- The straps may be attached by looping or by screws, but in the latter case an insert must be welded for each mounting point.

These inserts must be positioned in the reinforcement tube and the straps must be attached to them using bolts of M12 8.8 (ISO standard, minimum) or 7/16 UNF specification.

Each anchorage point must be able to withstand a load of 1470 daN, or 720 daN for the crotch straps.

In the case of one anchorage point for two straps (prohibited for shoulder straps), the load considered must be equal to the sum of the required loads.

For each new anchorage point created, a steel reinforcement plate with a surface area of at least 40 cm² and a thickness of at least 3 mm must be used.

The effectiveness and longevity of safety harnesses are directly related to the manner in which they are installed, used and maintained.

They must also be replaced if metal parts or buckles are bent, deformed or rusted.

86.02 Seat harnesses release

Two belt cutters must always be carried on board (identified with a sign). They must be easily accessible for the driver and co-driver when seated with their harnesses fastened.

Furthermore, it is recommended that for competitions which include public road sections, the harnesses be equipped with push-button release systems.

01.87 BODYPANEL

The vehicle must be fitted with its original body panel with possible local modifications (safety items ...).

A roof for the protection of the crew is compulsory, minimum thickness shall be of minimum 2 mm if it is made of steel or aluminium alloy, and of minimum 3 mm when made from other materials.

All parts of the body panel must be carefully and fully finished, with no temporary or makeshift parts and no sharp corners.

No part of the body panel may present sharp edges or points.

No mechanical component may be visible from above with the exception of shock absorbers, suspension arms, transversal driveshaft's, radiators, fans, wheels and spare wheels, including their anchorage points and attachments.

All parts having an aerodynamic influence and all parts of the body panel must be secured rigid to the completely sprung part of the vehicle (chassis/body unit); they must not have any degree of freedom, must be securely fixed and must remain immobile in relation to this part when the vehicle is in motion, with exception of the driver's and/or co-driver's ventilation sliders / scoops.

87.01 Exterior

The maximum overall length is 3550 mm without spare wheels.

The maximum width of the body panel is 1900 mm without rear view mirrors and/or spare wheels.

A windscreen is optional. However, should there be one; it must be made of laminated glass regardless of its shape and surface.

87.02 Lateral windows

Free, but it must be possible to remove the front doors or the windows of the front doors from inside the cockpit without the use of tools.

87.03 Windscreen wipers, motor and mechanism

These items are free.

87.04 Windscreen washer tank

The capacity and the position of the windscreen washer tank is free. The pumps, lines and nozzles are free.

87.05 Rear view mirrors

The vehicle must be fitted with two rear view mirrors, one on each side of the car, to provide efficient views to the rear. Each mirror must have a minimum area of 90 cm².

87.06 Rear camera

One rear view camera is permitted provided if it is non-swivelling.

87.07 Wheelbase

Must remain identical to the standard vehicle ± 50 mm.

87.08 Front and rear tracks

Must remain identical to the standard vehicle ± 50 mm.

87.09 Front and rear overhangs

Identical to the standard vehicle ± 50 mm (spare wheels, mudflaps and their supports not included).

87.10 Aerodynamic device

Identical to the standard vehicle /no modification authorised.

87.11 Underbody protections

The fitting of underbody protections is authorised on the following conditions:

- They must respect the ground clearance
- They must be removable
- They must protect only the following parts: engine, radiator, intercooler, gearbox, centre differential, rear differential, driveshaft's (longitudinal and transversal), subchassis, suspension parts, steering and exhaust line.

01.88 INTERIOR

88.01 Interior safety

The cockpit must be designed to ensure the comfort and safety of driver and possible co-drivers. No part may present sharp edges or points.

No mechanical part may protrude into the interior of the cockpit. Any equipment that could involve a risk must be protected or insulated and must not be situated in the cockpit.

The cars must have lateral openings allowing the exit of the driver / co-driver.

88.02 Inspection hatches

Inspection hatches are authorised in the bulkheads of the cockpit.

88.03 Bulkhead

A leakproof and flameproof bulkhead made of steel or aluminium alloy (minimum thickness 2 mm) or in composite material (minimum thickness 5 mm) is compulsory behind the seats and must be fully in contact with the main rollbar of the safety cage.

88.04 Protection nets

Cars without side windows must be fitted with lateral protection nets affixed to these doors using a quick release system situated on the lower part. The use of "clip" fixings is recommended. The fixings of the net on the upper part must not be removable without the use of tools.

These nets must have the following characteristics:

- Minimum width of the strips: 19 mm
- Minimum size of the meshes: 25 x 25 mm
- Maximum size of the meshes: 60 x 60 mm

and, viewed from the side, must reach from the centre of the steering wheel to the rearmost point of the seat on the side concerned.

88.05 Cooling of the cockpit

The ducts channelling air into the cockpit must be made of fire-retardant materials. Electric fans are allowed inside these ducts to enhance air circulation.

01.89 TRANSMISSION

The complete transmission (except otherwise specified) of the standard vehicle must be kept without modification.

A modification is only allowed, in order to de-activate the active systems if necessary.

All the parts must be available, as spare parts, through the Manufacturer's commercial network.

89.01 Transmission shaft

Transmission shafts are free but must be made of steel. In addition, they must be solid and in one piece and the joints must come from a series vehicle.

The transmission shaft location must be identical to the standard vehicle and must respect the following conditions:

- It may be situated inside or outside the cockpit.
- The floor of the cockpit must be closed with a metallic sheet, minimum thickness 1.5 mm.
- The metallic sheet must be securely fixed to the chassis.

89.02 The transmission tunnel

The installation of a transmission tunnel is mandatory if the transmission shaft is located inside the cockpit and can be modified with the following conditions:

- It must enclose the longitudinal shaft over the complete length of the cockpit.
- It must be made from a steel sheet of minimum thickness 1.5 mm, or from a steel tube of minimum thickness 3.0 mm.
- The transmission tunnel must be securely fixed to the floor or the chassis in such a way as to ensure that it cannot be detached during normal use or in case of an accident.
- The entire surface of the transmission tunnel must be free of any kind of hole, with the exception of the part attaching it to the floor or chassis.

If fitted outside the cockpit, a minimum of two steel safety straps, of minimum thickness 3.0 mm and minimum length 250 mm, must be fitted to each longitudinal shaft to prevent it from hitting the ground in case of breakage.

Should any fuel or oil tank be close to a longitudinal shaft, it is compulsory that the tank has extra protection in the walls close to the shaft.

89.03 Pedal box

Identical to the standard vehicle but the axis of the pedal box must be situated behind or directly above the axis of the front wheels.

89.04 Gearbox

Modification authorised on the gearbox / differential housing is allowed only to install an additional lubrication system.

89.04.01 CVT sytem

Identical to the standard vehicle / no modification authorised.

The belt is free provided that it is available as a spare part (reinforced or not) through the Manufacturer's commercial network.

A system for cooling the belt by air is authorised.

89.04.02 Manual or semi automatic or automatic operation control

Identical to the standard vehicle / no modification authorised.

89.04.03 Gearshift control

Gear shift type is free.

The gear shift lever must be fixed on the floor or on the steering column and can be adjustable. If fixed on the steering column the link between the gear lever and the gearbox must not be by cable or electric wires in case of semi-automatic or automatic control.

89.04.04 Cut-off sensor for gear command

Identical to the standard vehicle / no modification authorised.

89.04.05 Lubrication

An additional lubrication and oil cooling device is allowed (circulation pump, radiator and air intakes)

89.04.06 Clutch

Free, but principle and diameter must remain identical to the standard vehicle / no modification authorised.

89.04.07 Control system

Hydraulic or mechanic or other. Identical to the standard vehicle / no modification authorised.

The clutch stop (clutch release bearing) is free.

89.04.08 Master-cylinder and tank

Master cylinder and hydraulic oil reservoir are free.

89.04.09 Supports for Gearbox / CVT / Differentials

Supports are free.

01.90 MINIMUM WEIGHT

No Minimum weight

01.91 ENGINE

The maximum cylinder capacity is set at 1050 cm³ for normally aspirated engines and for supercharged engines. The engine of the standard vehicle must be kept as original without modifications.

91.01 Positions and inclination of the engine

Identical to the standard vehicle / no modification authorised.

91.02 Engine supports

Supports are free.

91.03 Plastic shields

Engine shields made of plastic material, the purpose of which is to hide mechanical components in the engine compartment, may be removed if they have a solely aesthetic function.

91.04 Screws, nuts and bolts

A nickel-based alloy may be used for the fixing of the exhaust manifold to the cylinder head.

91.05 Gaskets

All gaskets are free.

91.06 Cylinder head gasket

Identical to the standard vehicle / no modification authorised.

91.07 Ignition

The make and type of the spark plugs and leads are free.
The use of ceramics for spark plugs is authorised.

91.08 Fuel injection system

91.08.01 Fuel rail

Free.

91.08.02 Injectors

Identical to the standard vehicle / no modification authorised.

91.08.03 Electronic control unit (ECU) and engine control software

The ECU is free but the electronic control unit must come from a large scale production catalogue or from a competition parts catalogue.

91.08.04 Sensors

Sensors shall be identical to the standard vehicle / no modification authorised.

91.08.05 Actuators

Identical to the standard vehicle / no modification authorised.

91.09 Air intake system

91.09.01 Air filter

The choice of air filter element and its position is free. The plenum chamber and the lines between the restrictor / manifold and the atmosphere are free. Engine intake air must not be taken from inside the cockpit and any modifications must not affect the structure of the vehicle.

91.10 Supercharging system

Identical to the standard vehicle.

The dimensions of supercharger/turbo are free, but the exhaust mounting flange must be the same as the original part.

91.11 Pressure regulation valve (waste gate) / System for injecting air into the exhaust manifold

These parts must remain identical as fitted on to the standard vehicle / no modifications authorised.

91.12 Exhaust line

The exhaust exit(s) must be horizontal and situated within the perimeter of the vehicle defined by the chassis, body panels, roll cage and mud flap brackets.

The exits of the exhaust system must be visible from outside.

91.13 Heat shielding of the exhaust system

Heat shielding elements on the exhaust system or on components in close proximity to the exhaust system are authorised, but must be removable.

91.14 Cooling system

The original water pump must be retained.

91.15 Coolant radiator

The position of the coolant radiator is free but forbidden in the cockpit. The fans and their position are free, as are their electric looms.

91.16 Coolant lines

The expansion chambers are free, provided that the capacity of the new chambers does not exceed 2 litres and that they are not located in the cockpit.

The liquid cooling lines external to the engine block and their accessories are free.

91.17 Lubrication system

Radiator, oil/water exchanger, lines, thermostat, filter and pump strainers are free.

Oil pressure may be increased by changing the discharge valve spring.

If the lubrication system includes an open type sump breather, it must be equipped in such a way that the oil flows into a catch tank (minimum capacity: 1 litre).

The fitting of one or several ventilators for cooling the engine oil is authorised, provided that this does not have any aerodynamic effect.

91.18 Oil sump

Identical to the standard vehicle / no modification authorised.

91.19 Exchanger (intercooler) of the supercharging system

91.19.01 Intercooler

Identical to the standard vehicle / no modification authorised.

91.19.02 Supports and position of the heat exchanger

Support brackets and their position are free but are forbidden to be placed inside the cockpit.

91.19.03 Fans for cooling the exchanger

Identical to the standard vehicle / no modification authorised.

91.19.04 Cooling air ducts of the exchanger

Cooling air ducts are free.

91.19.05 Piping

The pipes between the supercharging device, the intercooler and the manifold are free (on condition that they remain in the engine bay), but their only function must be to channel air and to join various parts together.

The internal diameter of this (these) pipe(s) of the standard vehicle is considered as the maximum size permitted.

91.19.06 Accessories

Except for the components mentioned in Art. 91.17 Lubrication System, the following accessories must derive from a homologated vehicle engine or from a commercial catalogue and be available for sale to the public:

- alternator
- air conditioning compressor
- air compressors
- fuel pumps
- hydraulic pumps

The number and position of these accessories are free provided that they remain within the engine compartment and/or within the main structure of the vehicle. They may not be placed within the cockpit area. Their method of operation drive systems is free.

Local machining and/or welding of an accessory is permitted for its fitting and/or function.

01.92 ELECTRICAL EQUIPMENT

92.01 Wiring loom & Fuses

All wiring loom (using appropriate size and diameter) and fuses are free.

92.02 Circuit breakers

Circuit breakers may be freely changed vis-à-vis their use, position, or number in the case of additional accessories. The general circuit breaker must be a spark-proof model and must cut all electrical circuits, battery, alternator or dynamo, lights, horns, ignition, electrical controls, etc. and must also stop the engine.

At least three circuit breakers must be installed:

- One inside the cockpit: It must be accessible from inside the vehicle by the driver and the co-driver seated and secured by their safety harnesses

- Two outside the cockpit: one on either side of the bottom of the windscreen pillars and must be easily accessible even if the vehicle is lying on its side or roof.

92.03 Battery

92.03.01 Number

Identical to the standard vehicle / no modification authorised.

92.03.01 Type

The make, capacity and cables of the battery are free. The nominal voltage must be the same or lower than that of the standard vehicle. The minimum weight of the battery is 3 kg.

92.03.01 Location

The location of the battery(ies) is free, but the battery must be of the dry type if it is in the cockpit.

92.03.01 Fixation

Each battery must be securely fixed and the positive terminal must be protected.

Should the battery be moved from its original position, it must be attached to the body using a metal seat and two metal clamps with an insulating covering, fixed by bolts and nuts.

For attaching these clamps, metallic bolts with a diameter of at least 10 mm must be used, and under each bolt, a counter plate at least 3 mm thick and with a surface of at least 20 cm² beneath the metal of the body panel.

Wet batteries can be used, but must be placed and covered in a leakproof box, attached independently of the battery. The box must be attached independently to the chassis. The securing system must be able to withstand a deceleration of 25 g.

92.04 Starter

92.04.01 Location

Identical to the standard vehicle / no modification authorised.

92.04.02 Make and type

Identical to the standard vehicle / no modification authorised.

92.05 Data acquisition system

A competitor data recording system is authorised, but only the following sensors are allowed:

- sensors fitted on the reference vehicle
- 3 temperature sensors (engine oil, engine water, gearbox or CVT)
- pressure sensors (1 oil and 1 fuel)
- 1 engine knocking sensor (only if fitted on standard engine)
- 1 fuel level gauge for each fuel tank
- any sensors necessary for the navigation system allowed by the supplementary regulations of the competition
- wheel speed sensors (maximum 2), only on driven wheels.

92.06 Sensors

Any radar system, vehicle speed measurement system (except pulse ring on the gearbox), gyroscope, load sensor (except sensor for engine ignition and/or injection cut-off) or restraining gauge is forbidden.

Accelerometers are authorised for data logging only on condition they are built into the dash display equipment.

92.07 Transmission of data

The transmission of data by WI-FI, radio and/or telemetry is prohibited.

01.93 SUSPENSION

93.01 Suspension type

It is forbidden to use active suspension (any system which allows control of flexibility, damping, height and/or attitude of the suspension when the vehicle is in motion).

93.02 Wishbones/suspension arms

Free but must be interchangeable (without modification) with those of the standard vehicle.

93.03 Joints (wishbones/links and suspension parts)

Rubber, ball joint, plain bearing, bearings (ball, roller, needle) : free

93.04 Hubcarriers/wheel bearings/wheel hubs

Identical to the standard vehicle / no modification authorised.

93.05 Connection the hubcarrier and the wishbone

Identical to the standard vehicle / no modification authorised.

93.06 Springs and shock absorbers

Only one shock absorber per wheel is authorised. Shock absorbers are free but their mounting points to the chassis must remain identical as on the reference vehicle.

Any adjustment of the springs and/or shock absorbers from the cockpit is forbidden. Adjustment is only possible when the vehicle is not in motion and only with the use of hand tools. The adjustment device must be situated on the shock absorber or its gas reserve.

Any connections between dampers are forbidden, the only connections permitted are the shock absorber fixing points passing through the chassis; these must have no other function.

93.07 Springs

A coil spring may be replaced with two or more springs of the same type, concentric or in series, provided that they can be fitted without any modifications other than those specified in this article.

93.08 Antiroll bars / fixings

Free, but only one antiroll bar per axle is permitted.

The adjustment of the antiroll bars from the cockpit is forbidden.

The antiroll bar systems must be exclusively mechanical, with no activation or deactivation possible.

Any connections between front and rear antiroll bars are forbidden.

01.94 WHEELS

The fitting of air extractors on the wheels is prohibited.

94.01 Rims

The rims and bead lock devices must be made of steel or aluminium alloy.

Wheel trims are forbidden

94.02 Tyres

The tires must be off-road type with a maximum diameter of 770 mm (complete wheel) measured at 1,2 [bar] and dismantled from the vehicle.

The use of tyres intended for motorcycles is forbidden.

The fitting of intermediate parts between the rims and the tyres is forbidden.

Only one air valve is allowed per wheel and it must be fixed to the rim by a single hole, which has a maximum diameter of 12 mm and is positioned on the outer face of the rim.

94.03 Fixation

A bolted "Beadlock" device is allowed.

Central nut wheel fixing is forbidden.

Wheel fixations by bolts may be freely changed to fixations by pins and nuts.

The wheels do not have to be of the same diameter.

Hub and nut protections are permitted.

94.04 System for inflating / deflating the tyres

The use of any system for inflating / deflating the tyres when the vehicle is in motion is forbidden. The inflating / deflating operation must only be carried out while the vehicle is not in motion.

The only system authorised is a system connected to the wheels through a flexible tube during the operation and connected to one valve per wheel.

In order to adjust the tyre pressure, any air going in or out must pass through a conventional complete and unmodified VG5 type valve coming from a series light utility vehicle.

The tube and its inflating manometer may be situated in the cockpit on condition that the operating pressure is lower than 10 bars.

The system may be fed by a 12V electric compressor and/or by compressed air bottles.

94.04.01 Compressed bottles

If the system to inflate the tyres is composed by compressed air bottles it must follow these restrictions:

- Maximum capacity 3 litres each
- The mountings must be able to withstand a deceleration of 25 g
- Must not be situated in the cockpit.
- Must be positioned transversally in the vehicle

- Secured by at least two metal strap each

94.05 Spare wheel

The vehicle must be fitted with minimum one, maximum 2 spare wheel, free positions.

01.95 BRAKING SYSTEM

95.01 Control system

The pedal must normally control all the wheels and it is activated and controlled only by the driver. It includes at least two independent circuits operated by the same pedal (between the brake pedal and the callipers, the two circuits must be separately identifiable, without any interconnection other than the mechanical braking force balancing device).

The pressure is identical on the wheels of the same axle, with the exception of the pressure generated by the handbrake.

95.02 Brake disks

All the wheels must have a brake disk. The discs must come from a series vehicle or from a catalogue of competition parts. Their maximum diameter is set at 290 mm.

95.03 Callipers

The callipers must come from a series vehicle or from a catalogue of competition parts with a maximum of 4 pistons.

Mounting spacers for brake callipers is free

95.04 Master-cylinders and tanks

Free

95.05 Proportional valve

Free

95.06 Pedal box

Original / No modification allowed

95.07 Handbrake

Free.

If the original vehicle is fitted with a handbrake, the function must be kept.

01.96 STEERING

96.01 General

The link between the driver and the wheels must be mechanical and continuous.

4-wheel steering is prohibited.

96.02 Steering wheel

The steering wheel may be removable from the steering column through a quick release mechanism. This mechanism must consist of a flange concentric to the steering wheel axis, coloured yellow and installed on the steering column behind the steering wheel.

The release must be operated by pulling the flange along the steering wheel axis. Push buttons and switches may be fitted.

Padding in the form of 60-240 g/m² material, with a minimum thickness of 40 mm, must be fitted on the steering wheel over a minimum surface of 20 000 mm² (200 cm²) to protect the driver's face.

96.03 Steering mechanism

Identical to the standard vehicle / no modification authorised.

96.04 Steering mechanism position

Identical to the standard vehicle / no modification authorised.

96.05 Steering rods / Steering joints

Free but must be interchangeable (without modification) with those of the standard vehicle.

96.06 Steering column

Free but if the reference vehicle is must be fitted with an unmodified OEM (Original Equipment Manufacturer) energy absorbing device, it must be kept (without modification).

The locking system of the anti-theft steering lock must be rendered inoperative.

96.07 Support / steering column

Free.

96.08 Power steering

Identical to the standard vehicle / no modification authorised.

96.08.01 Oil cooling

Oil radiators, as well as a system for circulating the oil without generating pressure, are authorised.

96.08.02 Oil tank

Free.

01.97 FIRE EXTINGUISHERS

97.01 General

All vehicles must be fitted with one or two manual fire extinguishers.

The following information must be visible on each extinguisher:

- Capacity
- Type of fire extinguisher
- Weight or volume of the fire extinguisher
- Date the fire extinguisher was checked, which must be no more than two years after either the date of filling or the date of the last check, or corresponding expiry date.

All extinguishing equipment must withstand fire.

97.02 Permitted fire extinguisher

AFFF, FX G-TEC, Viro3, powder or any other fire extinguisher homologated.

97.03 Minimum quantity

- AFFF 2.4 litres
- FX G-TEC 2.0 kg
- Viro3 2.0 kg
- Zero 360 2.0 kg
- Powder 2.0 kg

97.04 Pressure

All extinguishers must be pressurised according in accordance with the manufacturer's instructions except for powder extinguishers with a pressure of 8 [bar] minimum and 13.5 [bar] maximum.

Furthermore, each extinguisher when filled with AFFF must be equipped with a mean of checking the pressure of the contents.

97.05 Location

At least one of the extinguishers must be easily accessible for the driver and the co-driver(s), seated normally with safety harnesses fastened and steering wheel in place.

All extinguishers must be adequately protected. The container may also be situated in the luggage compartment on condition that it is at least 300 mm from the outer edges of the bodypanel in all horizontal directions.

97.06 Fixation

It must be secured by a minimum of 2 screw-locked metallic straps and the securing system must be able to withstand a deceleration of 25 g.

Furthermore, only quick-release metal fastenings, with metal straps, are accepted. The material of the securing system must operate within the -15°C to +80°C temperature range.

97.07 Pipes

Plastic pipes are prohibited and metal pipes are mandatory (unless specified otherwise).

97.08 Triggering

The means of triggering must be marked with a letter "E" in red inside a white circle of at least 10 cm diameter with a red edge.

97.09 Nozzle

The injector nozzles shall be free of sharp, sharp contact and its nozzles shall not be facing towards the occupants.

97.10 Safety pin

The extinguisher safety pin must be removed before starting for the selective sectors, easily visible and marked with a red tape of 20x200mm (as shown below). This procedure will always be checked by the stewards at the start as well as at any other time during the qualifying sections. Failure to comply with this safety procedure will result in penalties to be set by the jury.



01.98 LIGHTS

98.01 General

The lighting equipment must be approved according to the ECE R38 road standard (or an equivalent or stricter standard from another country) or approved by recognised federation.

All forward facing lamps of more than 32 cm² surface area must be adequately protected and secured in case of glass breakage, by a grille or additional translucent panel.

98.02 Mandatory lights

Each vehicle must be fitted with at least:

- 2 headlights (combined passing lights/headlights)
- 2 front lamps
- 2 rear lamps and number plate lighting
- 2 stop lights with a minimum surface of 50 [cm²]
- 4 flashing indicators, two at the front and two at the rear
- Distress lights (Warning)
- 2 additional red rear fog lamps twinned or placed side by side with a minimum height of 1.25 [m] from the ground attached to the outside of the vehicle.

98.03 Additional lights

Two additional headlights may be fitted, provided that they are not situated more than 250 mm above the base of the windscreen.

They may be housed inside the supports of the external rear view mirrors.

The two headlamps and the additional lamps must be located in front of the axis of the front wheels, at a maximum height corresponding to that of the line of the bonnet/bottom of the windscreen (8 lamps maximum).

01.99 PILOT EQUIPMENT


The compulsory clothing equipment per occupant is: fire retardant suit, fireproof boots and fireproof gloves. The use of "HANS" system (including the helmet) is compulsory. It is not allowed to drive without the use of mandatory elements during the classification sections.

99.01 Helmets

The helmets must conform to the following standards:


- SNELL SA 2010
- SNELL SAH 2010
- SNELL SA 2015
-

Diagrams




QUADS	GROUP G (2WD)	GROUP H (4WD)
Max. overall width (mm)	1.300	1.400
Max. rim diameter (inches)	12	15
Max. seat height (mm)	950	1.000
Handlebar width (min-max, mm)	650	800


max overall width 1.400 mm (Group H)
max overall width 1.300 mm (Group G)



min 600 mm
max 850 mm



max overall width 1.400 mm (Group H)
max overall width 1.300 mm (Group G)




wheel rim
diameter
max 12" (Group G)
max 15" (Group H)


DIAGRAMME Q (suite)

PROTECTIVE DEVICES (REAR) : sprocket and disc
SYSTEMES DE PROTECTION (AR): couronne et disque

- (1) Chain guard, mounting to a height corresponding to minimum 90°
Sabot inférieur remontant à la hauteur correspondant à 90° minimum




- (2) Chain guard + (3) protective guard
Sabot inférieur + (3) barre de protection



NUMBERS / NUMEROS

0



TEN FITTING TESTS FOR HELMETS **DIX TESTS D'ADAPTATION POUR LES CASQUES**

1. *Obtain correct size by measuring the crown of the head*
Avoir la bonne grandeur en mesurant le sommet de la tête
2. *Check there is no side to side movement*
Vérifier qu'il n'y ait pas de déplacement d'un côté à l'autre
3. *Tighten strap securely*
Serrer solidement la jugulaire
4. *With head forward, attempt to pull up back of helmet to ensure helmet cannot be removed this way*
Tête en avant, essayer de soulever le casque pour s'assurer qu'il ne peut pas être enlevé de cette façon



5. *Check ability to see clearly over shoulder*
Vérifier si vous pouvez voir clairement par-dessus l'épaule
6. *Make sure nothing impedes your breathing in the helmet and never cover your nose or mouth*
S'assurer que rien ne gêne votre respiration dans le casque et ne jamais couvrir le nez ou la bouche
7. *Never wind scarf around neck so that air is stopped from entering the helmet. Never wear scarf under the retention strap*
Ne jamais enrouler une écharpe autour du cou, car cela empêche l'air d'entrer dans le casque. Ne jamais porter d'écharpe sous la jugulaire
8. *Ensure that visor can be opened with one gloved hand*
S'assurer que la visière peut être ouverte avec une main gantée
9. *Satisfy yourself that the back of your helmet is designed to protect your neck*
S'assurer que l'arrière de votre casque a une forme telle qu'il vous protège la nuque
10. *Always buy the best you can afford*
Toujours acheter le meilleur que vous pouvez vous offrir



FÉDÉRATION INTERNATIONALE
DE MOTOCYCLISME

FIM-LIVE.com

11, ROUTE DE SUISSE | CH - 1295 MIES
cti@fim.ch

6579008